

**Problem 1** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int a[4] = {3, 31, 314, 3141};
    int a2[2][2] = {{3, 31}, {314, 3141}};
    int b = 3, c = 1;

    cout << min(b, 4) << endl;           // (a) prints: 3
    swap(b, c);                          // (b) swaps b and c
    a[0] = max(a, 4);                    // (c) sets a[0] to 3141
    cout << second(a2, 2, 2) << endl;    // (d) prints: 314
    makeZero(a2[1][1]);                  // (e) makes it 0
    return 0;
}
```

(a) Title line for **min** as called at the line marked (a).

**Answer:**

(b) Title line for **swap** as called at the line marked (b).

**Answer:**

(c) Title line for **max** as called at the line marked (c).

**Answer:**

(d) Title line for **second** as called at the line marked (d).

**Answer:**

(e) Title line for **makeZero** as called at the line marked (e).

**Answer:**

**Problem 2** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int up(int x[], int c) {
    if (c == 1) cout << x[1];
    if (c < 2) return 23;
    if (c == 2) return x[1];
    return x[c] + up(x, c - 1);
}

int main() {
    int x[6] = {3, 1, 4, 1, 5, 9};
    cout << 3 + x[1] << endl;           // line (a)
    for (int i = 0; i < 6; i++) cout << x[i];    cout << endl; // line (b)
    cout << up(x, 1) << endl;           // line (c)
    cout << up(x, 2) << x[2] << endl;    // line (d)
    cout << up(x, 4) << endl;           // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 3** Write a function called *averageOdd* that returns the average of all of the odd numbers in a 2-dimensional array with 3 columns. If no odd numbers are present, it should return a result of 0. Excessively long solutions that use more than 15 lines of code may lose points.

For example, a program that uses the function *averageOdd* follows.

```
int main() {
    int data[2][3] = {{3, 1, 4},{2, 7, 1}};
    cout << averageOdd(data, 2, 3) << endl;    // prints 3.0
                                                // because the odd entries 3, 1, 7, 1 average to 3.0
    return 0;
}
```

**Answer:**

**Problem 4** Write a function called *interlaceDigits* that uses two positive integer parameters with the same number of digits and returns an integer that begins with the first digit of the first parameter, then the first digit of the second parameter, then the second digits of the parameters, and so on until all digits are used. If a negative parameter is given, or if parameters with unequal numbers of digits are given your function can return any result of your choosing. Excessively long solutions that use more than 10 lines of code may lose points.

For example, a program that uses the function *interlaceDigits* follows.

```
int main() {
    cout << interlaceDigits(1, 2) << endl;           // prints 12
    cout << interlaceDigits(117, 302) << endl;      // prints 131072
    cout << interlaceDigits(1357, 2468) << endl;    // prints 12345678
    return 0;
}
```

**Answer:**

**Problem 5** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int i = 123, arr1 [3] = {1, 2, 3}, arr2 [2][2] = {{1, 0}, {2, 4}};
    double d1 = 1.23, d2 = 12.3;
    printLine (arr2, 2, 2);           // (a) prints: 1 0 2 4
    printFancy (arr1, 3);             // (b) prints: 1 * 2 ** 3 ***
    cout << doNothing (i, (int) d1); // (c) prints: This is a useless function
    switchValues (d1, d2);           // (d) switches the values: now, d1 = 12.3, d2 = 1.23
    goodDayWishes ();                // (e) prints: Have a good day
    return 0;
}

```

(a) Title line for **printLine** as called at the line marked (a).

**Answer:**

(b) Title line for **printFancy** as called at the line marked (b).

**Answer:**

(c) Title line for **doNothing** as called at the line marked (c).

**Answer:**

(d) Title line for **switchValues** as called at the line marked (d).

**Answer:**

(e) Title line for **goodDayWishes** as called at the line marked (e).

**Answer:**

**Problem 6** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int up(int x[], int c) {
    if (c == 1) cout << x[1];
    if (c < 2) return 47;
    if (c == 2) return x[1];
    return x[c] + up(x, c - 1);
}

int main() {
    int x[6] = {2, 7, 1, 8, 2, 8};
    cout << 3 + x[1] << endl;           // line (a)
    for (int i = 0; i < 6; i++) cout << x[i];    cout << endl; // line (b)
    cout << up(x, 1) << endl;           // line (c)
    cout << up(x, 2) << x[2] << endl;    // line (d)
    cout << up(x, 4) << endl;           // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 7** Write a function called *numberNegative* that returns the number of negative elements in a 2-dimensional array with 3 columns. Excessively long solutions that use more than 12 lines of code may lose points.

For example, a program that uses the function *numberNegative* follows.

```
int main() {
    double data[2][3] = {{-3.0, 1, 4.5},{-2.2, 7, 1.4}};
    cout << numberNegative(data, 2, 3) << endl;    // prints 2
                                                // because there are 2 negatives -3.0 and -2.2
    return 0;
}
```

**Answer:**

**Problem 8** Write a function called *interweaveDigits* that uses two positive integer parameters with the same number of digits and returns an integer that begins with the first digit of the second parameter, then the first digit of the first parameter, then the second digits of the parameters, and so on until all digits are used. If a negative parameter is given, or if parameters with unequal numbers of digits are given your function can return any result of your choosing. Excessively long solutions that use more than 10 lines of code may lose points.

For example, a program that uses the function *interweaveDigits* follows.

```
int main() {
    cout << interweaveDigits(2, 1) << endl;           // prints 12
    cout << interweaveDigits(302, 117) << endl;       // prints 131072
    cout << interweaveDigits(2468, 1357) << endl;     // prints 12345678
    return 0;
}
```

**Answer:**

**Problem 9** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int a[4] = {3, 31, 314, 3141};
    int a2[2][2] = {{3, 31}, {314, 3141}};
    int b = 3, c = 1;

    cout << min(b, 4) << endl;           // (a) prints: 3
    swap(b, c);                          // (b) swaps b and c
    a[0] = max(a, 4);                     // (c) sets a[0] to 3141
    cout << second(a2, 2, 2) << endl;     // (d) prints: 314
    makeZero(a2[1][1]);                   // (e) makes it 0
    return 0;
}
```

(a) Title line for **min** as called at the line marked (a).

**Answer:**

(b) Title line for **swap** as called at the line marked (b).

**Answer:**

(c) Title line for **max** as called at the line marked (c).

**Answer:**

(d) Title line for **second** as called at the line marked (d).

**Answer:**

(e) Title line for **makeZero** as called at the line marked (e).

**Answer:**

**Problem 10** Consider the following C++ program.

```
#include <iostream>
using namespace std;

void up(int x[][3], int rows, int cols) {
    for (int c = 0; c < cols; c++) for (int r = 0; r < rows; r++)
        cout << 10 + x[r][c];
    cout << endl;
}

int main() {
    int x[3][3] = {{3, 1, 4}, {1, 5, 9}, {2, 6, 5}};
    cout << x[2][2] << endl; // line (a)
    cout << x[x[2][0]][x[2][0]] << endl; // line (b)
    for (int r = 0; r < 2; r++) cout << x[2][r] << endl; // line (c)
    up(x, 1, 1); // line (d)
    up(x, 2, 2); // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 11** Write a function called *sum3* that returns the sum of all of the 3-digit numbers in an array. Excessively long solutions that use more than 12 lines of code may lose points.

For example, a program that uses the function *sum3* follows.

```
int main() {
    int x[6] = {3, 31, 314, 111, 4000, 100};
    cout << sum3(x, 6) << endl; // prints 525
    // because the 3-digit numbers 314, 111, 100 add to 525
    return 0;
}
```

**Answer:**

**Problem 12** Write a function called *gcb* that uses two positive integer parameters and returns the greatest common beginning to the two numbers. For example, the greatest common beginning of 1235 and 1248 is 12. If the two parameters begin differently the function should return 0. If a negative parameter is given your function can return any result of your choosing. Excessively long solutions that use more than 10 lines of code may lose points.

For example, a program that uses the function *gcb* follows.

```
int main() {
    cout << gcb(123, 223) << endl;           // prints 0
    cout << gcb(117, 119) << endl;           // prints 11
    cout << gcb(1357, 136578) << endl;       // prints 13
    return 0;
}
```

**Answer:**

**Problem 13** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int i = 123, arr1 [3] = {1, 2, 3}, arr2 [2][2] = {{1, 0}, {2, 4}};
    double d1 = 1.23, d2 = 12.3;
    printLine (arr2, 2, 2);                 // (a) prints: 1 0 2 4
    printFancy (arr1, 3);                   // (b) prints: 1 * 2 ** 3 ***
    cout << doNothing (i, (int) d1); // (c) prints: This is a useless function
    switchValues (d1, d2); // (d) switches the values: now, d1 = 12.3, d2 = 1.23
    goodDayWishes ();                       // (e) prints: Have a good day
    return 0;
}
```

(a) Title line for **printLine** as called at the line marked (a).

**Answer:**

(b) Title line for **printFancy** as called at the line marked (b).

**Answer:**

(c) Title line for **doNothing** as called at the line marked (c).

**Answer:**

(d) Title line for **switchValues** as called at the line marked (d).

**Answer:**

(e) Title line for **goodDayWishes** as called at the line marked (e).

**Answer:**

**Problem 14** Consider the following C++ program.

```
#include <iostream>
using namespace std;

void up(int x[][3], int rows, int cols) {
    for (int c = 0; c < cols; c++) for (int r = 0; r < rows; r++)
        cout << x[r][c] - 7;
    cout << endl;
}

int main() {
    int x[3][3] = {{2, 7, 1}, {8, 2, 8}, {1, 8, 2}};
    cout << x[2][2] << endl; // line (a)
    cout << x[x[2][0]][x[2][0]] << endl; // line (b)
    for (int r = 0; r < 2; r++) cout << x[2][r] << endl; // line (c)
    up(x, 1, 1); // line (d)
    up(x, 2, 2); // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 15** Write a function called *numberFreddy* that returns the number of entries of an array equal to "Freddy". Excessively long solutions that use more than 12 lines of code may lose points.

For example, a program that uses the function *numberFreddy* follows.

```
int main() {
    string data[5] = {"Kelly", "Jack", "Freddy", "Arthur", "Freddy"};
    cout << numberFreddy(data, 5) << endl;    // prints 2
    return 0;
}
```

**Answer:**

**Problem 16** Write a function called *gce* that uses two positive integer parameters and returns the greatest common ending to the two numbers. For example, the greatest common ending of 1234 and 134 is 34. If the two parameters end differently the function should return 0. If a negative parameter is given your function can return any result of your choosing. Excessively long solutions that use more than 10 lines of code may lose points.

For example, a program that uses the function *gce* follows.

```
int main() {
    cout << gce(123, 123) << endl;           // prints 123
    cout << gce(123, 223) << endl;           // prints 23
    cout << gce(117, 119) << endl;           // prints 0
    cout << gce(1357, 13657) << endl;        // prints 57
    return 0;
}
```

**Answer:**

**Problem 17** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    char x = 'a', y = 'b', z = 'c';
    string a[3] = {"A", "B", "Freddy"};
    bool b[2][2] = {{true, false},{true,true}};
    int c = 0;

    c = subtract(z, y);           // (a) sets c to the difference 1
    welcomeUser(a[2]);           // (b) print out "Hello Freddy"
    deFred(a[2]);                // (c) change it to "Anon"
    reset(b, 2, 2, 2 == 2);      // (d) sets the array to be all true
    cout << addOn(addOn(a[2],x),y); // (e) function adds on a character
    return 0;
}

```

(a) Title line for **subtract** as called at the line marked (a).

**Answer:**

(b) Title line for **welcomeUser** as called at the line marked (b).

**Answer:**

(c) Title line for **deFred** as called at the line marked (c).

**Answer:**

(d) Title line for **reset** as called at the line marked (d).

**Answer:**

(e) Title line for **addOn** as called at the line marked (e).

**Answer:**

**Problem 18** Consider the following C++ program.

```

#include <iostream>
using namespace std;

void up(int x[][3], int rows, int cols) {
    for (int c = 0; c < cols; c++) for (int r = 0; r < rows; r++)
        cout << (char) ('A' + x[r][c]);
    cout << endl;
}

void recursive(int x[][3], int r) {
    if (r == 0) {
        cout << endl;
        return;
    }
    cout << x[r - 1][r - 1];
    recursive(x, r - 1);
}

int main() {
    int x[3][3] = {{3, 1, 4}, {1, 5, 9}, {2, 6, 5}};
    cout << x[1][1] << x[0][2] << endl;           // line (a)
    cout << x[x[1][0]][x[1][0]] << endl;         // line (b)
    for (int c = 0; c < 3; c++) cout << x[2][c] << endl; // line (c)
    up(x, 2, 2);                                 // line (d)
    recursive(x,3);                              // line (e)
}

```



(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 19** Write a function called *goodStudent* that gives the name of a student who scores at least 8 points on a quiz. The function uses three parameters: an array of names, an array of scores and a count of students. If more than one student scores at least 8, the first name in the array with a score of at least 8 is returned. If no student does well a result of "Nobody" is returned.

For example, a program that uses the function *goodStudent* follows.

```
int main() {
    string students[4] = {"Freddy", "Kelly", "Arthur", "Jack"};
    int scores[4] = {0, 8, 7, 10};
    int hardQuiz[4] = {0, 1, 1, 2};
    cout << goodStudent(students, scores, 4) << endl; // prints Kelly
    cout << goodStudent(students, hardQuiz, 4) << endl; // prints Nobody
    return 0;
}
```

**Answer:**

**Problem 20** Write a function called *biggerDigits* that uses two positive integer parameters with the same number of digits and returns an integer whose digit in each position is the bigger of the two digits in that position in the input parameters. If a negative parameter is given, or if parameters with unequal numbers of digits are given your function can return any result of your choosing.

For example, a program that uses the function *biggerDigits* follows.

```
int main() {
    cout << biggerDigits(567, 765) << endl; // prints 767
    cout << biggerDigits(123456, 444444) << endl; // prints 444456
    cout << biggerDigits(999, 111) << endl; // prints 999
    return 0;
}
```

**Answer:**

**Problem 21** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    string x = "a", y = "b", z = "c";
    char a[3] = {'A', 'B', 'C'};
    int b[2][2] = {{1,0},{1, 1}};
    bool c = false;

    c = sameLength(x, y, "z");           // (a) sets c to true
    courseName(a[2]);                    // (b) print out "A course about C"
    cout << plusplus(a, 2);              // (c) print "A++ B++ C++"
    reset(b, 2, 2, a[2] - a[0]);        // (d) sets all array entries to 2
    cout << addOn(addOn(z,a[0]),a[0]);   // (e) function adds on a character
    return 0;
}

```

(a) Title line for **sameLength** as called at the line marked (a).

**Answer:**

(b) Title line for **courseName** as called at the line marked (b).

**Answer:**

(c) Title line for **plusplus** as called at the line marked (c).

**Answer:**

(d) Title line for **reset** as called at the line marked (d).

**Answer:**

(e) Title line for **addOn** as called at the line marked (e).

**Answer:**

**Problem 22** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int recursive(int x[][3], int r) {
    if (r <= -1) return 1;
    return x[r][r] + recursive(x, r - 1);
}

int main() {
    int x[3][3] = {{2, 7, 1}, {8, 2, 8}, {1, 8, 2}};
    cout << x[1][2] << x[2][1] << endl;           // line (a)
    cout << x[x[1][1]][x[0][0]] << endl;         // line (b)
    for (int c = 0; c < 3; c++) cout << x[c][c] << endl; // line (c)
    cout << recursive(x, -1) << endl;           // line (d)
    cout << recursive(x, 1) << endl;           // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 23** Write a function called *bestStudents* that prints the names of all students that get the highest score on a quiz. The function uses three parameters: an array of names, an array of scores and a count of students.

For example, a program that uses the function *bestStudents* follows.

```
int main() {
    string students[4] = {"Freddy", "Kelly", "Arthur", "Jack"};
    int scores[4] = {0, 1, 1, 1};
    bestStudents(4, scores, students);    // prints Kelly Arthur Jack
    return 0;
}
```

**Answer:**

**Problem 24** Write a function called *digitDifference* that uses two positive integer parameters with the same number of digits and returns an integer whose digit in each position is the (positive) difference between the two digits in that position in the input parameters. If a negative parameter is given, or if parameters with unequal numbers of digits are given your function can return any result of your choosing.

For example, a program that uses the function *digitDifference* follows.

```
int main() {
    cout << digitDifference(567, 765) << endl;           // prints 202
    cout << digitDifference(123456, 444444) << endl;      // prints 321012
    cout << digitDifference(999, 111) << endl;           // prints 888
    cout << digitDifference(999, 987) << endl;           // prints 12
    return 0;
}
```

**Answer:**

**Problem 25** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    string name = "Freddy Next Door";
    int a2[2][3] = {{-2, 4, 3}, {-3, 4, 2}};
    int a[5] = {7, 6, 5, 9, 7};
    cout << firstLetters(name, name) << endl;           // (a) prints: F F
    cout << sumAll(a, 5, a, 5) << endl;                 // (b) prints: 68 by summing twice
    cout << middleInitial(name) << endl;               // (c) prints: N
    makeRandom(a2, 2, 3);                               // (d) reset the array with random entries
    if (countIt(name, countIt(middleInitial(name), 5.0)) > 0) // (e) mystery
        cout << "Yes\n";
    return 0;
}

```

(a) Title line for **firstLetters** as called at the line marked (a).

**Answer:**

(b) Title line for **sumAll** as called at the line marked (b).

**Answer:**

(c) Title line for **middleInitial** as called at the line marked (c).

**Answer:**

(d) Title line for **makeRandom** as called at the line marked (d).

**Answer:**

(e) Title line for **countIt** as called at the line marked (e).

**Answer:**

**Problem 26** Write blocks of code to perform the functions used in the following main program. Your blocks must match the given title lines. Each block should be a short function of only a few lines.

```

int main() {
    int b = 1, c = 2, a[4] = {3, 1, 4, 1}, x = 10, y = 1000;
    // (a) Finds the cube, here -27
    cout << cube(-3) << endl;
    // (b) Finds a random number between 1 and x
    cout << random(x) << endl;
    // (c) Prints the ratio as a percentage, here 12.5% for 1/8
    cout << percentage(1, 8) << "%" << endl;
    // (d) reverse print the array here 1413 (no spaces)
    reversePrint(a, 4);
    // (e) determine whether x or y has more digits, assume x and y both positive
    if (hasMore(x,y)) cout << "x is longer\n";
    return 0;
}

```

(a) int cube(int x)

**Answer:**

(b) int random(int x)

**Answer:**

(c) double percentage(int x, int y)

**Answer:**

(d) void reversePrint(int x[], int cap)

**Answer:**

(e) bool hasMore(int x, int y)

**Answer:**

**Problem 27** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int xy(int x, string &y) {
    if (x > 0) y = "error";
    else y = "fine";
    if (x <= 0) return 3;
    return x % 10 + 10 * xy(x/10, y);
}

int main() {
    int c = 9, x = 10;
    string y;
    if ((x % c) >= (c % x)) cout << c;           // line (a)
    cout << endl;
    for(c = 8; c > x - c; c--) cout << c;       // line (b)
    cout << endl;
    cout << xy(-2, y) << endl;                   // line (c)
    cout << y << endl;                           // line (d)
    cout << xy(3145, y) << endl;                 // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 28** Write a function called *toNumber* that uses an array of integers each entry of which is between 0 and 9 and returns an integer formed by using the entries as its digits. If input array entries are out of range, you can return any answer of your choosing. Your function should not use more than 5 lines of code.

For example, a program that uses the function *toNumber* follows.

```
int main() {
    int a[6] = {3,1,4,1,5,9};
    cout << toNumber(a, 6) << endl;           // prints 314159
    cout << toNumber(a, 6) + 1 << endl;       // prints 314160
    return 0;
}
```

**Answer:**

**Problem 29** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int i = 2;
    int x[5] = {3, 1, 4, 1, 5};
    cout << max(2.1, i, 1.5) << endl;           // (a) prints 2.1
    cout << min(x[2], x[3]) << endl;           // (b) prints 1
    negateIt(i); cout << i + 1 << endl;       // (c) prints -1
    printArray(x, 5);                          // (d) prints 31415
    if (sum(sum(2.1, 6), 1) > 0) cout << "big\n"; // (e) prints big
    return 0;
}

```

(a) Title line for **max** as called at the line marked (a).

**Answer:**

(b) Title line for **min** as called at the line marked (b).

**Answer:**

(c) Title line for **negateIt** as called at the line marked (c).

**Answer:**

(d) Title line for **printArray** as called at the line marked (d).

**Answer:**

(e) Title line for **sum** as called at the line marked (e).

**Answer:**

**Problem 30** Consider the following C++ program.

```

#include <iostream>
using namespace std;

double sum(int x[], int cap, int jump) {
    double ans = 0.0;
    for (int i = 0; i < cap; i+= jump)
        ans += x[i];
    return ans / 10.0;
}

int main() {
    int x[6] = {2, 1, 3, 0, 4, 9};
    cout << x[2] << endl;           // line (a)
    cout << x[5/3] << endl;         // line (b)
    cout << x[x[2]] << endl;        // line (c)
    cout << sum(x, 6, 1) << endl;    // line (d)
    cout << sum(x, 4, 2) << endl;    // line (e)
    return 0;
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 31** Write a function called *maxGap* that calculates the largest gap between adjacent entries of an array. (A gap between two numbers is the absolute value of their difference.)

For example, a program that uses the function *maxGap* follows.

```
int main() {
    int x[5] = {2, 9, 1, 6, 3};
    cout << maxGap(x, 5) << endl;    // prints 8 corresponding to the gap from 1 to 9.
    return 0;
}
```

**Answer:**

**Problem 32** Write a function called *secondDown* that returns the result of decreasing the second digit of a positive integer parameter by 1. (If the second digit is already 0, then the value of the parameter is returned. If the parameter is less than 10, then the function can return any answer of your choice.)

For example, a program that uses the function *secondDown* follows.

```
int main() {
    cout << secondDown(243) << endl;    // prints 233
    cout << secondDown(2048) << endl;    // prints 2048
    cout << secondDown(1234) + 1 << endl;    // prints 1135
    return 0;
}
```

**Answer:**

**Problem 33** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int i = 3;
    string s = "Hello";
    int x[5] = {2, 7, 1, 8, 2};
    cout << min(i, 2.1, x[0]) << endl;    // (a) prints: 2.1
    cout << max(x[2], 3) << endl;        // (b) prints: 3
    cout << doubleIt(i) << endl;        // (c) prints: 2 x 3
    hi(s); cout << s << endl;          // (d) prints: Hi
    cout << sum(sum(2,6,i), i, i) << endl;    // (e) prints: 17
    return 0;
}
```

(a) Title line for **min** as called at the line marked (a).

**Answer:**

(b) Title line for **max** as called at the line marked (b).

**Answer:**

(c) Title line for **doubleIt** as called at the line marked (c).

**Answer:**

(d) Title line for **hi** as called at the line marked (d).

**Answer:**

(e) Title line for **sum** as called at the line marked (e).

**Answer:**

**Problem 34** Consider the following C++ program.

```
#include <iostream>
using namespace std;

double sum(int x[], int cap, int jump) {
    double ans = 0.0;
    for (int i = 0; i < cap; i+= jump)
        ans += x[i];
    return ans / 5.0;
}

int main() {
    int x[6] = {5, 4, 3, 2, 1, 9};
    cout << x[3] << endl;           // line (a)
    cout << x[5/3] << endl;         // line (b)
    cout << x[x[3]] << endl;        // line (c)
    cout << sum(x, 6, 1) << endl;   // line (d)
    cout << sum(x, 5, 2) << endl;   // line (e)
    return 0;
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 35** Write a function called *sumGaps* that calculates the sum of the gaps between adjacent entries of an array. (A gap between two numbers is the absolute value of their difference.)

For example, a program that uses the function *sumGaps* follows.



```
int main() {
    int x[5] = {3, 1, 4, 1, 5};
    cout << sumGaps(x, 5) << endl;    // prints 12 corresponding to the sum of gaps 2 + 3 + 3 + 4.
    return 0;
}
```

**Answer:**

**Problem 36** Write a function called *thirdDown* that returns the result of decreasing the third digit of a positive integer parameter by 1. (If the third digit is already 0, then the value of the parameter is returned. If the parameter is less than 100, then the function can return any answer of your choice.)

For example, a program that uses the function *thirdDown* follows.

```
int main() {
    cout << thirdDown(1243) << endl;    // prints 1233
    cout << thirdDown(12048) << endl;    // prints 12048
    cout << thirdDown(11234) + 1 << endl;    // prints 11135
    return 0;
}
```

**Answer:**

**Problem 37** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int i = 2;
    double x[5] = {3.0, 1.1, 4.2, 1.3, 5.4};
    cout << max(4.1, x[i] / 10, i) << endl;    // (a) prints 4.1
    cout << min(x[2], x[3]) << endl;    // (b) prints 1.3
    squareIt(i); cout << i << endl;    // (c) prints 4
    squareAll(x, 5); cout << x[0] << endl;    // (d) prints 9.0
    if (f(f(x[0])) > 2) cout << "+" << endl;    // (e) prints +
    return 0;
}
```

(a) Title line for **max** as called at the line marked (a).

**Answer:**

(b) Title line for **min** as called at the line marked (b).

**Answer:**

(c) Title line for **squareIt** as called at the line marked (c).

**Answer:**

(d) Title line for **squareAll** as called at the line marked (d).

**Answer:**

(e) Title line for **f** as called at the line marked (e).

**Answer:**

**Problem 38** Consider the following C++ program.

```

#include <iostream>
using namespace std;

void down(int x[], int cap, int gap) {
    for (int i = 0; i < cap; i+= gap)
        x[i] -= gap;
}

int main() {
    int x[6] = {3, 1, 4, 1, 5, 9};
    cout << x[5] / 4 << endl;           // line (a)
    cout << x[5/4] << endl;           // line (b)
    cout << x[x[5]/4] << endl;       // line (c)
    down(x, 6, 1); cout << x[1] << endl; // line (d)
    down(x, 6, 3); cout << x[1] << endl; // line (e)
    return 0;
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 39** Write a function called *evenSum* that calculates the sum of those entries in an array that are even numbers.

For example, a program that uses the function *evenSum* follows.

```

int main() {
    int x[8] = {3, 1, 4, 1, 5, 9, 2, 6};
    cout << evenSum(x, 8) << endl; // prints 12
    // The even entries are 4, 2, 6 and these add to 12
    return 0;
}

```

**Answer:**

**Problem 40** Write a function called *allEven* that reports whether all the digits in a positive integer parameter are even.

For example, a program that uses the function *allEven* follows.

```

int main() {
    int x;
    cout << "Enter a number: ";
    cin >> x;
    if (allEven(x)) cout << "All digits are even." << endl;
    else cout << "Not all digits are even." << endl;
    return 0;
}

```

If the user entered any of 2, 242 or 2048, the program would print *All digits are even*. But if the user entered any of 1, 21, 1248 or 555, the program would print *Not all digits are even*.

**Answer:**

**Problem 41** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    double x = 0.0, y = 1.1, z = 2.5;
    int array[5] = {3,1,4,1,5};
    string s = "Hello";

    z = average(x, y, z);           // (a) sets z to average 1.2
    addStar(s);                     // (b) replaces s by "Hello*"
    cout << bigger(average(x,y,z), 7.5); // (c) prints 7.5 because it is bigger
    cout << endl;
    printArray(array, 5);           // (d) prints array: 3 1 4 1 5
    subtract(array[0], array, 5);   // (e) subtracts array[0] from other elements
    printArray(array, 5);           // output will now be 0 -2 1 -2 2
    return 0;
}
```

(a) Title line for **average** as called at the line marked (a).

**Answer:**

(b) Title line for **addStar** as called at the line marked (b).

**Answer:**

(c) Title line for **bigger** as called at the line marked (c).

**Answer:**

(d) Title line for **printArray** as called at the line marked (d).

**Answer:**

(e) Title line for **subtract** as called at the line marked (e).

**Answer:**

**Problem 42** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int fun(int x, int &y) {
    if (x < 0) y = -x;
    if (x <= 0) return 0;
    return x % 10 + 2 * fun(x/100, y);
}

int main() {
    int c, x = 1, y = 5;
    if ((x % y) > (y % x)) cout << x;           // line (a)
    cout << endl;
    for(c = x; c < y; c++) cout << c;           // line (b)
    cout << endl;
    cout << fun(-2, y) << endl;                 // line (c)
    cout << y << endl;                           // line (d)
    cout << fun(31459, y) << endl;               // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 43** Write a function called *subtractFirst* that subtracts the value of the first element from every element in an array.

For example, a program that uses the function *subtractFirst* follows.

```
int main() {
    int array[6] = {3,1,4,1,5,9};
    subtractFirst(array, 6);
    for (int i = 0; i < 6; i++)
        cout << array[i] << " ";    // Output will be 0 -2 1 -2 2 6
    return 0;
}
```

**Answer:**

**Problem 44** Write a function called *cutAfter7* that cuts a positive integer parameter after the first digit 7 that it contains. Parameters that are not positive should be returned without any change.

For example, a program that uses the function *cutAfter7* follows.

```
int main() {
    cout << cutAfter7(765) << endl;    // prints 7
    cout << cutAfter7(765765) << endl; // prints 7
    cout << cutAfter7(666) << endl;    // prints 666
    cout << cutAfter7(107) << endl;    // prints 107
    cout << cutAfter7(107007) << endl; // prints 107
    return 0;
}
```

**Answer:**

**Problem 45** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    double z = 2.5;
    int array[5] = {3,1,4,1,5};
    string s = "Hello";

    z = average(array, 5);           // (a) sets z to average 2.8
    addTwice(s,"**");               // (b) replaces s by "Hello**Hello**"
    cout << sum(average(array, 5), 1.2); // (c) 4.0 the sum of 1.2 and the average
    cout << endl;
    cout << someArray(array, 3);     // (d) prints 3 elements: 3 1 4
    count(array[1], array, 5);      // (e) print count of copies of array[1] in array
    return 0;
}

```

(a) Title line for **average** as called at the line marked (a).

**Answer:**

(b) Title line for **addTwice** as called at the line marked (b).

**Answer:**

(c) Title line for **sum** as called at the line marked (c).

**Answer:**

(d) Title line for **someArray** as called at the line marked (d).

**Answer:**

(e) Title line for **count** as called at the line marked (e).

**Answer:**

**Problem 46** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int xy(int x, string &y) {
    if (x < 0) y = "error";
    else y = "ok";
    if (x <= 0) return 5;
    return x % 10 + 10 * xy(x/100, y);
}

int main() {
    int c = 4, x = 1;
    string y;
    if ((x % c) == (c % x)) cout << c;           // line (a)
    cout << endl;
    for(c = 5; c > x; c--) cout << c;           // line (b)
    cout << endl;
    cout << xy(-2, y) << endl;                   // line (c)
    cout << y << endl;                           // line (d)
    cout << xy(31459, y) << endl;                 // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 47** Write a function called *subtractAverage* that subtracts the average value of an array from every element in an array.

For example, a program that uses the function *subtractAverage* follows.

```
int main() {
    double array[6] = {3,1,4,1,5};    // has average 2.8
    subtractAverage(array, 5);
    for (int i = 0; i < 5; i++)
        cout << array[i] << " ";    // Output will be 0.2 -1.8 1.2 -1.8 2.2
    return 0;
}
```

**Answer:**

**Problem 48** Write a function called *cutBefore7* that cuts a positive integer parameter before the first digit 7 that it contains. Parameters that are not positive should be returned without any change.

For example, a program that uses the function *cutBefore7* follows.

```
int main() {
    cout << cutBefore7(667) << endl;    // prints 66
    cout << cutBefore7(677) << endl;    // prints 6
    cout << cutBefore7(666) << endl;    // prints 666
    cout << cutBefore7(766) << endl;    // prints 0
    cout << cutBefore7(567567) << endl; // prints 56
    return 0;
}
```

**Answer:**

**Problem 49** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    string s; char c = 'A'; double d = 1.1;
    int a[4] = {3, 1, 4, 2};
    bool b[2][3] = {{true, false, true}, {false, true, true}};

    s = asString(c); cout << s << endl;        // (a) prints: A
    doubleIt(d); cout << d << endl;           // (b) prints: 2.2
    doubleThem(a, 4); cout << a[0] << endl;    // (c) prints 6
    printArray(b, 2, 3);                       // (d) prints TFT FTT
    c = randomLetter(); cout << c << endl;    // (e) prints a random letter eg Z
    return 0;
}

```

(a) Title line for **asString** as called at the line marked (a).

**Answer:**

(b) Title line for **doubleIt** as called at the line marked (b).

**Answer:**

(c) Title line for **doubleThem** as called at the line marked (c).

**Answer:**

(d) Title line for **printArray** as called at the line marked (d).

**Answer:**

(e) Title line for **randomLetter** as called at the line marked (e).

**Answer:**

**Problem 50** Consider the following C++ program.

```

#include <iostream>
using namespace std;

double down(int x[], int cap, int gap) {
    double ans = 0.0;
    for (int i = 0; i < cap; i+= gap)
        ans += x[i];
    return ans / 10;
}

int main() {
    int x[4] = {3, 1, 4, 1};
    cout << x[2] << endl;                // line (a)
    cout << x[5/3] << endl;              // line (b)
    cout << down(x, 4, 1) << endl;      // line (c)
    cout << down(x, 4, 3) << endl;      // line (d)
    cout << down(x, x[0], x[x[1]]) << endl; // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 51** Write a function called *diff2* that returns the absolute value of the difference of the first two digits of a positive integer parameter. If the parameter has just one digit, that digit should be returned.

For example, a program that uses the function *diff2* follows.

```
int main() {
    cout << diff2(7070);      // prints 7
    cout << endl;
    cout << diff2(7907);      // prints 2
    cout << endl;
    cout << diff2(7);         // prints 7
    cout << endl;
    return 0;
}
```

**Answer:**

**Problem 52** Write a function called *evenLessOdd* that returns the sum of the even valued entries minus the sum of the odd valued entries in an array of integers.

For example, a program that uses the function *evenLessOdd* follows. The first output is  $2 = 8 - 1 - 5$  and the second is  $-10 = -1 - 1 - 5 - 3$ .

```
int main() {
    int x[3] = {8, 1, 5};
    int y[4] = {1, 1, 5, 3};
    cout << evenLessOdd(x, 3) << endl;      // prints 2
    cout << evenLessOdd(y, 4) << endl;      // prints -10
    return 0;
}
```

**Answer:**

**Problem 53** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**



```

int main() {
    string s; char c = 'A'; double d = 1.1;
    int a[4] = {3, 1, 4, 2};
    bool b[2][3] = {{true, false, true}, {false, true, true}};

    d = randomNumber(); cout << d << endl; // (a) prints a random number eg 1.5
    printThem(a, 4); // (b) prints 3142
    b[1][0] = majority(b, 2, 3); if (b[1][0]) cout << "true\n"; // (c) prints true
    doubleIt(a[1]); cout << a[1] << endl; // (d) prints: 2
    s = asString(b[0][0]); cout << s << endl; // (e) prints: True
    return 0;
}

```

(a) Title line for **randomNumber** as called at the line marked (a).

**Answer:**

(b) Title line for **printThem** as called at the line marked (b).

**Answer:**

(c) Title line for **majority** as called at the line marked (c).

**Answer:**

(d) Title line for **doubleIt** as called at the line marked (d).

**Answer:**

(e) Title line for **asString** as called at the line marked (e).

**Answer:**

**Problem 54** Consider the following C++ program.

```

#include <iostream>
using namespace std;

double down(int x[], int cap, int &gap) {
    double ans = 0.0;
    for (int i = 0; i < cap; i+= gap)
        ans += x[i];
    gap += 2;
    return ans / 10;
}

int main() {
    int x[4] = {3, 2, 1, 8};
    int a = 4, b = 1;
    cout << x[7/3] << endl; // line (a)
    cout << down(x, a, b) << endl; // line (b)
    cout << down(x, a, b) << endl; // line (c)
    cout << down(x, x[0], x[x[2]]) << endl; // line (d)
    cout << x[2] << endl; // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 55** Write a function called *unlucky* that returns an answer of *true* if the first two digits of a positive integer parameter add to 13. Otherwise it returns *false*. (It returns *false* if the parameter has fewer than 2 digits.)

For example, a program that uses the function *unlucky* follows.

```
int main() {
    if (unlucky(6789)) cout << "Unlucky!\n"; // prints Unlucky!
    if (unlucky(6889)) cout << "Unlucky!\n"; // prints
    if (unlucky(6)) cout << "Unlucky!\n"; // prints
    if (unlucky(49)) cout << "Unlucky!\n"; // prints Unlucky!
    return 0;
}
```

**Answer:**

**Problem 56** Write a function called *lastOdd* that returns the last odd valued entry in an array or returns 0 if there is no odd value.

For example,

```
int main() {
    int x[3] = {8, 1, 7};
    int y[5] = {1, 2, 5, 4, 6};
    int z[2] = {2, 2};
    cout << lastOdd(x, 3) << endl; // prints 7
    cout << lastOdd(y, 5) << endl; // prints 5
    cout << lastOdd(z, 2) << endl; // prints 0
    return 0;
}
```

**Answer:**

**Problem 57** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    string s; char c = 'A'; double d = 4.0;
    int a[4] = {3, 1, 4, 2};
    bool b[2][3] = {{true, false, true}, {false, true, true}};

    printThem(b, 2, 3); // (a) prints TFT FTT
    fixLies(b, 2, 3); printThem(b, 2, 3); // (b) prints FTF TFF
    d = cubeIt(d); cout << d << endl; // (c) prints: 64.0
    cubeInt(a[2]); cout << a[2] << endl; // (d) prints: 64
    a[1] = reverseDigits(a[2]); cout << a[1] << endl; // (e) prints: 1
    return 0;
}

```

(a) Title line for **printThem** as called at the line marked (a).

**Answer:**

(b) Title line for **fixLies** as called at the line marked (b).

**Answer:**

(c) Title line for **cubeIt** as called at the line marked (c).

**Answer:**

(d) Title line for **cubeInt** as called at the line marked (d).

**Answer:**

(e) Title line for **reverseDigits** as called at the line marked (e).

**Answer:**

**Problem 58** Consider the following C++ program.

```

#include <iostream>
using namespace std;

double down(int x[], int cap, int &gap) {
    double ans = 0.0;
    for (int i = 0; i < cap; i+= gap)
        ans += x[i];
    gap += 2;
    return ans / 10;
}

int main() {
    int x[4] = {9, 1, 3, 2};
    int a = 4, b = 2;
    cout << x[9/3] << endl; // line (a)
    cout << down(x, a, b) << endl; // line (b)
    cout << down(x, a, b) << endl; // line (c)
    cout << down(x, x[2], x[x[2]]) << endl; // line (d)
    cout << x[3] << endl; // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 59** Write a function called *add7* that returns an answer found by putting a 7 in front of the first digit of a positive integer.

For example, a program that uses the function *add7* follows.

```
int main() {
    cout << add7(1) << "\n";    // prints 71
    cout << add7(17) << "\n";   // prints 717
    cout << add7(456) << "\n";  // prints 7456
    return 0;
}
```

**Answer:**

**Problem 60** Write a function called *indexFirstOdd* that returns the index of the first odd valued entry in an array or returns -1 if there is no odd value. (The index of an entry is its position in the array.)

For example,

```
int main() {
    int x[3] = {8, 8, 7};
    int y[5] = {7, 2, 5, 1, 9};
    int z[2] = {2, 2};
    cout << indexFirstOdd(x, 3) << endl;    // prints 2
    cout << indexFirstOdd(y, 5) << endl;    // prints 0
    cout << indexFirstOdd(z, 2) << endl;    // prints -1
    return 0;
}
```

**Answer:**

**Problem 61** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    string fullName = "Freddy Next Door";
    int a2[2][3] = {{-2, 4, 3}, {-3, 4, 2}};
    int a[5] = {7, 6, 5, 9, 7};
    cout << middleDigit(19683) + 1 << endl;    // (a) prints: 7 as 6 + 1
    cout << random(a2, 2, 3) << endl;        // (b) prints random entry eg 4
    cout << initials(fullName) << endl;     // (c) prints: F.N.D.
    makePositive(a2[0][0]);                 // (d) make a2[0][0] positive
    cout << number7s(a, 5);                 // (e) prints 2: the number of 7s
    return 0;
}

```

(a) Title line for **middleDigit** as called at the line marked (a).

**Answer:**

(b) Title line for **random** as called at the line marked (b).

**Answer:**

(c) Title line for **initials** as called at the line marked (c).

**Answer:**

(d) Title line for **makePositive** as called at the line marked (d).

**Answer:**

(e) Title line for **number7s** as called at the line marked (e).

**Answer:**

**Problem 62** Write the best **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    string fullName = "Freddy Next Door";
    int a2[2][3] = {{-2, 4, 3}, {-3, 4, 2}};
    int a[5] = {7, 6, 5, 9, 7};
    cout << firstLetter(fullName) << endl;    // (a) prints: F
    cout << sumFirstCol(a2, 2, 3) << endl;    // (b) prints: -5 (as -2 + - 3).
    cout << middleName(fullName) << endl;    // (c) prints: Next
    makeRandom(a2, 2, 3);                    // (d) reset the array with random entries
    cout << round(((double) a[0])/((double) a[1])); // (e) prints 1
                                                // the nearest integer to the ratio.
    return 0;
}

```

(a) Title line for **firstLetter** as called at the line marked (a).

**Answer:**

(b) Title line for **sumFirstCol** as called at the line marked (b).

**Answer:**

(c) Title line for **middleName** as called at the line marked (c).

**Answer:**

(d) Title line for **makeRandom** as called at the line marked (d).

**Answer:**

(e) Title line for **round** as called at the line marked (e).

**Answer:**

**Problem 63** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int fun(int &x, int y) {
    x = x + 1;
    y = y - 1;
    return y;
}

int main() {
    int x = 2, y = 7, z = 10;    string s = "007";
    cout << ((double) y) / x << endl;    // line (a)
    if (!(x > y) && (y > 5)) s = "008";
    cout << s << endl;    // line (b)
    z %= y; cout << z << endl;    // line (c)
    cout << fun(z, y) << endl;    // line (d)
    fun(x, y); cout << y - x * 2 << endl;    // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 64** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int fun(int x, int &y) {
    x = x + 1;
    y = y - 1;
    return y;
}

int main() {
    int x = 3, y = 9, z = 10;    string s = "Yes";
    cout << ((double) x) / z << endl;    // line (a)
    if (!(x > y) || (y > 5)) s = "No";
    cout << s << endl;    // line (b)
    z %= y; cout << z << endl;    // line (c)
    cout << fun(z, y) << endl;    // line (d)
    fun(x, y); cout << y - x % 2 << endl;    // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 65** Write a function called *removeLast0* that prints an integer parameter without its rightmost 0. If there is no 0, print the number itself. If the number is 0, print nothing.

For example, a program that uses the function *removeLast0* follows.

```
int main() {
    removeLast0(7070);          // prints 707
    cout << endl;
    removeLast0(7007);          // prints 707
    cout << endl;
    removeLast0(777);           // prints 777
    cout << endl;
    return 0;
}
```

**Answer:**

**Problem 66** Write a function called *removeLast7* that removes the rightmost 7 from an integer parameter. If there is no 7, it makes no change.

For example, a program that uses the function *removeLast7* follows.

```
int main() {
    cout << removeLast7(777) << endl;      // prints 77
    cout << removeLast7(1727) << endl;     // prints 172
    cout << removeLast7(1234) << endl;     // prints 1234
    return 0;
}
```

**Answer:**

**Problem 67** Write a function called *largestGap* that returns the largest gap between two adjacent elements of an array.

For example, a program that uses the function *largestGap* follows, it prints 7 since the largest gap is between the 9 and the 2.

```
int main() {
    int x[] = {3, 1, 4, 1, 5, 9, 2, 6};
    cout << largestGap(x, 8) << endl; // prints 7
    return 0;
}
```

**Answer:**

**Problem 68** Write a function called *smallestProduct* that returns the smallest product formed by two adjacent elements of an array.

For example, a program that uses the function *smallestProduct* follows, it prints 3 since the smallest product is between the 3 and the 1.

```
int main() {
    int x[] = {3, 1, 4, 1, 5, 9, 2, 6};
    cout << smallestProduct(x, 8) << endl; // prints 3
    return 0;
}
```

**Answer:**

**Problem 69** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int x = 0, y = 1, z = 2;
    double b[3] = {1.9, 2.3, 3.0};

    x = larger(x + y, z);           // (a) sets x as the larger
    x = largest(x, y, y, z);       // (b) sets x as the largest
    printAll(b, x, y);            // (c) print them all
    boost(x, y);                  // (d) increase x by the value of y
    boost(y, mystery(y, z));      // (e) boosts y by a mystery amount
    return 0;
}
```

(a) Title line for **larger** as called at the line marked (a).

**Answer:**

(b) Title line for **largest** as called at the line marked (b).

**Answer:**

(c) Title line for **printAll** as called at the line marked (c).

**Answer:**

(d) Title line for **boost** as called at the line marked (d).

**Answer:**

(e) Title line for **mystery** as called at the line marked (e).

**Answer:**

**Problem 70** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int x = 0, y = 1, z = 2;
    double b[3] = {1.9, 2.3, 3.0};

    larger(x + y, z);             // (a) prints the larger
    x = middle(x, y, y, z, z);   // (b) sets x as the middle value
    printAll(sqrt(b[1]), rand()); // (c) print them all
    swap(x, y);                  // (d) swap them
    cout << mystery(y, mystery(y, b[0])); // (e) a mystery function
    return 0;
}
```



(a) Title line for **larger** as called at the line marked (a).

**Answer:**

(b) Title line for **middle** as called at the line marked (b).

**Answer:**

(c) Title line for **printAll** as called at the line marked (c).

**Answer:**

(d) Title line for **swap** as called at the line marked (d).

**Answer:**

(e) Title line for **mystery** as called at the line marked (e).

**Answer:**

**Problem 71** Write blocks of code to perform the functions used in the following main program. Your blocks must match the given title lines. Each block should be a short function of only a few lines.

```
int main() {
    int b = 1, c = 2, a[4] = {3, 1, 4, 1};
    // (a) Prints the sum of 3 things, here 6
    cout << sum3(1,3,c) << endl;
    // (b) Prints decimal form of fraction b/c, here 0.5
    cout << fraction(b, c) << endl;
    // (c) Fill array with random integers
    randomFill(a, 4);
    // (d) Print array backwards, with entries separated by spaces
    backPrint(a, 4);
    // (e) Print the first digit, assume argument is positive. Here 1.
    firstDigit(19683);
    cout << endl;
    return 0;
}
```

(a) int sum3(int x, int y, int z)

**Answer:**

(b) double fraction (int x, int y)

**Answer:**

(c) void randomFill(int x[], int cap)

**Answer:**

(d) void backPrint(int x[], int cap)

**Answer:**

(e) void firstDigit(int x)

**Answer:**

**Problem 72** Write blocks of code to perform the functions used in the following main program. Your blocks must match the given title lines. Each block should be a short function of only a few lines.

```

int main() {
    int b = 1, c = 2, a[4] = {3, 1, 4, 1};
    // (a) Prints the average of 3 things, here 2.0
    cout << average3(1,3,c) << endl;
    // (b) Print the fraction b/c as a percentage, here 50.0%
    cout << percentage(b, c) << "%" << endl;
    // (c) Fill array with random positive single digit integers
    randomFill(a, 4);
    // (d) Print array, with entries separated by spaces
    print(a, 4);
    // (e) Print the second digit, assume argument is at least 10. Here print 9.
    cout << secondDigit(19683) << endl;
    return 0;
}

```

(a) double average3(int x, int y, int z)

**Answer:**

(b) double percentage(int x, int y)

**Answer:**

(c) void randomFill(int x[], int cap)

**Answer:**

(d) void print(int x[], int cap)

**Answer:**

(e) int secondDigit(int x)

**Answer:**

**Problem 73** Write a function called *gcd* that returns the greatest common divisor of two positive integers. For example, a program that uses the function *gcd* follows.

```

int main() {
    cout << gcd(10, 15) << endl;    // prints 5
    cout << gcd(11, 15) << endl;    // prints 1
    cout << gcd(0, 15) << endl;    // prints 15
    return 0;
}

```

**Answer:**

**Problem 74** Write a function called *removeFirst* that removes the first digit of a positive integer and returns the result (or returns 0 if the integer has only one digit).

For example, a program that uses the function *removeFirst* follows.

```

int main() {
    cout << removeFirst(19683) << endl;    // prints 9683
    cout << removeFirst(11) << endl;    // prints 1
    cout << removeFirst(1) << endl;    // prints 0
    return 0;
}

```

**Answer:**

**Problem 75** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

1. It asks the user to enter to enter 250 integers.
2. It computes the average of the 250 integers that the user supplies.
3. It prints out exactly those numbers entered by the user that differ from the average by no more than 10.

**Answer:**

**Problem 76** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

1. It asks the user to enter to enter 250 integers.
2. It prints out exactly the negative numbers entered by the user in the reverse of their order of input.

**Answer:**

**Problem 77** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int a[4] = {314, 315, 265, 358};
    int b = 1, c = 4;

    cout << max(a, 4) << endl;           // (a) prints: 358
    reverse(a, 4);                       // (b) prints: 358 265 315 314
    b = add(b, c);                        // (c) b becomes 5
    cout << difference(a[0], a[1]) << endl; // (d) prints: 1
    a[0] = sum(a[1], c);                  // (e) a[0] becomes 319
    return 0;
}
```

(a) Title line for **max** as called at the line marked (a).

**Answer:**

(b) Title line for **reverse** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **difference** as called at the line marked (d).

**Answer:**

(e) Title line for **sum** as called at the line marked (e).

**Answer:**

**Problem 78** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[4] = {314, 315, 265, 358};
    int b = 1, c = 4, capacity = 4;

    swap(b, c);                // (a) swaps values of b & c
    b = last(a, 4);           // (b) b becomes 358
    c = add(a[1], a[0]);      // (c) c becomes 629
    cout << max(a[1], 1) << endl; // (d) prints: 315
    cout << max(a, capacity, 700) << endl; // (e) prints 700
    return 0;
}

```

(a) Title line for **swap** as called at the line marked (a).

**Answer:**

(b) Title line for **last** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **max** as called at the line marked (d).

**Answer:**

(e) Title line for **max** as called at the line marked (e).

**Answer:**

**Problem 79** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[4] = {314, 315, 265, 358};
    int b = 1, c = 4;

    cout << max(4, a) << endl; // (a) prints: 358
    reverse(a, 4);           // (b) a becomes 358,265,315,314
    b = add(b, b, c);        // (c) b becomes 6
    cout << difference(a[1], 300) << endl; // (d) prints: 15
    addOn(a[1], c);         // (e) a[1] changes to 319
    return 0;
}

```

(a) Title line for **max** as called at the line marked (a).

**Answer:**

(b) Title line for **reverse** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **difference** as called at the line marked (d).

**Answer:**

(e) Title line for **addOn** as called at the line marked (e).

**Answer:**

**Problem 80** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[4] = {314, 315, 265, 358};
    int b = 1, c = 4, capacity = 4;

    swap(a[3], c);           // (a) swaps values of a[3] & c
    b = first(a);           // (b) b becomes 314
    a[3] = add(a[1], a[0]); // (c) a[3] becomes 629
    cout << min(a, capacity) << endl; // (d) prints: 265
    printMin(a, capacity); // (e) prints: 265
    return 0;
}

```

(a) Title line for **swap** as called at the line marked (a).

**Answer:**

(b) Title line for **first** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **min** as called at the line marked (d).

**Answer:**

(e) Title line for **printMin** as called at the line marked (e).

**Answer:**

**Problem 81** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[2][2] = {{314, 315}, {265, 358}};
    int b = 1, c = 4;

    cout << max(a, 2, 2) << endl;           // (a) prints: 358
    reverse(a, 2, 2);                       // (b) prints: 358 265 315 314
    b = add(b, c);                           // (c) b becomes 5
    cout << difference(a[0][0], a[0][1]) << endl; // (d) prints: 1
    a[0][0] = sum(a[0][1], c);               // (e) a[0][0] becomes 319
    return 0;
}

```

(a) Title line for **max** as called at the line marked (a).

**Answer:**

(b) Title line for **reverse** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **difference** as called at the line marked (d).

**Answer:**

(e) Title line for **sum** as called at the line marked (e).

**Answer:**

**Problem 82** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[2][2] = {{314, 315}, {265, 358}};
    int b = 1, c = 4, rows = 2, cols = 2;

    swap(b, c); // (a) swaps values of b & c
    b = last(a, rows, cols); // (b) b becomes 358
    c = add(a[0][1], a[0][0]); // (c) c becomes 629
    cout << max(a[0][1], 1) << endl; // (d) prints: 314
    cout << max(a, rows, cols, 700) << endl; // (e) prints 700
    return 0;
}

```

(a) Title line for **swap** as called at the line marked (a).

**Answer:**

(b) Title line for **last** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **max** as called at the line marked (d).

**Answer:**

(e) Title line for **max** as called at the line marked (e).

**Answer:**

**Problem 83** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[2][2] = {{314, 315}, {265, 358}};
    int b = 1, c = 4;

    cout << max(2, 2, a) << endl; // (a) prints: 358
    reverse(a, 2, 2); // (b) a becomes 358,265,315,314
    b = add(b, b, c); // (c) b becomes 6
    cout << difference(a[0][1], 300) << endl; // (d) prints: 15
    addOn(a[0][1], c); // (e) a[0][1] changes to 319
    return 0;
}

```

(a) Title line for **max** as called at the line marked (a).

**Answer:**

(b) Title line for **reverse** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **difference** as called at the line marked (d).

**Answer:**

(e) Title line for **addOn** as called at the line marked (e).

**Answer:**

**Problem 84** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[2][2] = {{314, 315}, {265, 358}};
    int b = 1, c = 4, row = 2, col = 2;

    swap(a[1][1], c);           // (a) swaps values of a[1][1] & c
    b = first(a);              // (b) b becomes 314
    a[1][1] = add(a[0][1], a[0][0]); // (c) a[1][1] becomes 629
    cout << min(a, row, col) << endl; // (d) prints: 265
    printMin(a, row, col);     // (e) prints: 265
    return 0;
}

```

(a) Title line for **swap** as called at the line marked (a).

**Answer:**

(b) Title line for **first** as called at the line marked (b).

**Answer:**

(c) Title line for **add** as called at the line marked (c).

**Answer:**

(d) Title line for **min** as called at the line marked (d).

**Answer:**

(e) Title line for **printMin** as called at the line marked (e).

**Answer:**

**Problem 85** Write blocks of code to perform the functions used in the following main program. Your blocks must match the given title lines. Each block should be a short function of only a few lines.

```

int main() {
    int b = 1, c = 2, a[4] = {3, 1, 4, 1};
    // (a) Prints the difference (ignoring sign), here 1
    cout << absoluteDifference(7,8) << endl;
    // (b) Prints random integer in range from b to c, assume b < c
    cout << random(b, c) << endl;
    // (c) Print square root of sum of squares of arguments, here 5.0
    cout << hyp(3, 4) << endl;
    // (d) Print array backwards, here 1413
    backPrint(a, 4);
    // (e) Print the last digit, assume argument is positive. Here 3.
    lastDigit(19683);
    return 0;
}

```

(a) int absoluteDifference(int x, int y)

**Answer:**

(b) int random(int x, int y)

**Answer:**

(c) double hyp(int x, int y)

**Answer:**

(d) void backPrint(int x[], int cap)

**Answer:**

(e) void lastDigit(int x)

**Answer:**

**Problem 86** Write blocks of code to perform the functions used in the following main program. Your blocks must match the given title lines. Each block should be a short function of only a few lines.

```
int main() {
    int b = 1, c = 2, a[4] = {3, 1, 4, 1};
    // (a) Prints the max, here 8
    cout << max(7,8) << endl;
    // (b) Swaps values
    swap(b, c);
    // (c) Print ratio, here 0.75
    cout << ratio(3, 4) << endl;
    // (d) Print number of even entries, here 1
    cout << countEven(a, 4) << endl;
    // (e) Print the first digit, assume argument is positive. Here 1.
    firstDigit(19683);
    return 0;
}
```

(a) int max(int x, int y)

**Answer:**

(b) void swap(int &x, int &y)

**Answer:**

(c) double ratio(int x, int y)

**Answer:**

(d) int countEven(int x[], int cap)

**Answer:**

(e) void firstDigit(int x)

**Answer:**

**Problem 87** Write blocks of code to perform the functions used in the following main program. Your blocks must match the given title lines. Each block should be a short function of only a few lines.

```
int main() {
    int b = 1, c = 2, a[4] = {3, 1, 4, 1};
    // (a) Prints the absolute value (ignore sign), here 7
    cout << absolute(-7) << endl;
    // (b) Prints a random id number with the given length, here 007 may be printed
    random(3);
    // (c) Prints the ratio as a percentage, here 12.5% for 1/8
    cout << percentage(1, 8) << "%" << endl;
    // (d) Print every second entry of the array here 34
    skipPrint(a, 4);
    // (e) Print the last two digit, assume argument is at least 10. Here 83.
    lastTwoDigits(19683);
    return 0;
}
```



(a) `int absolute(int x)`

**Answer:**

(b) `void random(int x)`

**Answer:**

(c) `double percentage(int x, int y)`

**Answer:**

(d) `void skipPrint(int x[], int cap)`

**Answer:**

(e) `void lastTwoDigits(int x)`

**Answer:**

**Problem 88** Write blocks of code to perform the functions used in the following main program. Your blocks must match the given title lines. Each block should be a short function of only a few lines.

```
int main() {
    int b = 1, c = 2, a[4] = {3, 1, 4, 1};
    // (a) Print the number of odd arguments, here 1
    cout << numberOdd(7,8) << endl;
    // (b) Reorder arguments so that they increase, here swap them
    sort(c, b);
    // (c) Print closest integer here 4
    cout << closest(3.75) << endl;
    // (d) Print maximum entry, here 4
    cout << max(a, 4) << endl;
    // (e) Print the first digit, assume argument is positive. Here 1.
    cout << firstDigit(19683) << endl;
    return 0;
}
```

(a) `int numberOdd(int x, int y)`

**Answer:**

(b) `void sort(int &x, int &y)`

**Answer:**

(c) `int closest(double x)`

**Answer:**

(d) `int max(int x[], int cap)`

**Answer:**

(e) `int firstDigit(int x)`

**Answer:**

**Problem 89** Write a function called *numEven* that returns the number of even digits in a positive integer parameter.

For example, a program that uses the function *numEven* follows.

```
int main() {
    cout << numEven(23) << endl;           // prints 1
    cout << numEven(1212) << endl;        // prints 2
    cout << numEven(777) << endl;        // prints 0
    return 0;
}
```

**Answer:**

**Problem 90** Write a function called *lastEven* that returns the last even digit in a positive integer parameter. It should return 0 if there are no even digits.

For example, a program that uses the function *lastEven* follows.

```
int main() {
    cout << lastEven(23) << endl;      // prints 2
    cout << lastEven(1214) << endl;    // prints 4
    cout << lastEven(777) << endl;    // prints 0
    return 0;
}
```

**Answer:**

**Problem 91** Write a function called *sumEven* that returns the sum of the even digits in a positive integer parameter.

For example, a program that uses the function *sumEven* follows.

```
int main() {
    cout << sumEven(23) << endl;      // prints 2
    cout << sumEven(1212) << endl;    // prints 4
    cout << sumEven(777) << endl;    // prints 0, because there are none
    return 0;
}
```

**Answer:**

**Problem 92** Write a function called *lastOdd* that returns the last odd digit in a positive integer parameter. It should return 0 if there are no odd digits.

For example, a program that uses the function *lastOdd* follows.

```
int main() {
    cout << lastOdd(23) << endl;      // prints 3
    cout << lastOdd(1254) << endl;    // prints 5
    cout << lastOdd(666) << endl;    // prints 0
    return 0;
}
```

**Answer:**

**Problem 93** Write a function called *firstEven* that returns the first even digit in a positive integer parameter. It should return -1 if there are no even digits.

For example, a program that uses the function *firstEven* follows.

```
int main() {
    cout << firstEven(23) << endl;    // prints 2
    cout << firstEven(1416) << endl;  // prints 4
    cout << firstEven(777) << endl;  // prints -1
    return 0;
}
```

**Answer:**

**Problem 94** Write a function called *evenLessOdd* that returns the sum of the even valued digit minus the sum of the odd valued digits in a positive integer parameter.

For example, a program that uses the function *evenLessOdd* follows.

```

int main() {
    cout << evenLessOdd(43) << endl;      // prints 1
    cout << evenLessOdd(9876) << endl;    // prints -2
    cout << evenLessOdd(777) << endl;    // prints -21
    return 0;
}

```

**Answer:**

**Problem 95** Write a function called *firstOdd* that returns the first odd digit in a positive integer parameter. It should return -1 if there are no odd digits.

For example, a program that uses the function *firstOdd* follows.

```

int main() {
    cout << firstOdd(21) << endl;        // prints 1
    cout << firstOdd(3456) << endl;    // prints 3
    cout << firstOdd(666) << endl;    // prints -1
    return 0;
}

```

**Answer:**

**Problem 96** Write a function called *oddLessEven* that returns the sum of the odd valued digits minus the sum of the even valued digits in a positive integer parameter.

For example, a program that uses the function *oddLessEven* follows.

```

int main() {
    cout << oddLessEven(23) << endl;    // prints 1
    cout << oddLessEven(1234) << endl; // prints -2
    cout << oddLessEven(777) << endl;  // prints 21
    return 0;
}

```

**Answer:**

**Problem 97** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int up(int a[][3], int x, int y) {
    if (a[x][y] % 2 == 0) cout << a[x][y] << endl;
    a[x][y]++;
    return a[x][y];
}

int main() {
    int x[2][3] = {{1,2,3}, {3,4,5}};
    cout << x[1][1] << endl;           // line (a)
    for (int i = 0; i < 2; i++) cout << x[i][i] << endl; // line (b)
    cout << x[x[0][0]][x[0][1]] << endl; // line (c)
    up(x,1,1);                        // line (d)
    cout << up(x,1,2) << endl;         // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 98** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int up(int a[][3], int x, int y) {
    if (y < 2) return a[x][y+1];
    cout << a[x][y] << endl;
    return a[x][y];
}

int main() {
    int x[2][3] = {{3,2,1}, {0,3,6}}, a = 0;
    cout << x[a][a] << endl; // line (a)
    for (int i = 0; i < 2; i++) cout << x[i][2 - i] << endl; // line (b)
    cout << x[x[x[0][2]][0]][0] << endl; // line (c)
    up(x,1,1); // line (d)
    cout << up(x,1,2) << endl; // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 99** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int up(int a[][3], int x, int y) {
    if (a[x][y] % 2 == 1) cout << a[x][y] << endl;
    a[x][y]++;
    return a[x][y];
}

int main() {
    int x[2][3] = {{0,1,2}, {4,5,6}}, a = 0;
    cout << x[1][1] << endl; // line (a)
    for (int i = 0; i < 2; i++) cout << x[i][i] << endl; // line (b)
    cout << x[x[0][0]][x[0][1]] << endl; // line (c)
    cout << up(x,1,1) << endl; // line (d)
    up(x,1,2); // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 100** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int up(int a[][3], int x, int y) {
    if (y < 2) return a[1-x][y+1];
    cout << a[x][y] << endl;
    return a[x][y];
}

int main() {
    int x[2][3] = {{2,1,0}, {0,4,8}}, a = 0;
    cout << x[a][2*a] << endl; // line (a)
    for (int i = 0; i < 2; i++) cout << x[i][i] << endl; // line (b)
    cout << x[0][x[x[0][1]][0]] << endl; // line (c)
    up(x,1,2); // line (d)
    cout << up(x,1,1) << endl; // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 101** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int up(int a[][2], int x, int y) {
    if (a[x][y] % 2 == 0) cout << a[x][y] << endl;
    a[x][y]++;
    return a[x][y];
}

int main() {
    int x[3][2] = {{1,2}, {3,3}, {4,5}};
    cout << x[1][1] << endl; // line (a)
    for (int i = 0; i < 2; i++) cout << x[i][i] << endl; // line (b)
    cout << x[x[0][1]][x[0][0]] << endl; // line (c)
    up(x,1,1); // line (d)
    cout << up(x,2,1) << endl; // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 102** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int up(int a[][2], int x, int y) {
    if (y < 1) return a[x][y+1];
    cout << a[x][y] << endl;
    return a[x][y];
}

int main() {
    int x[3][2] = {{3,2},{4,5},{0,1}}, a = 0;
    cout << x[a][a] << endl; // line (a)
    for (int i = 0; i < 2; i++) cout << x[2 - i][i] << endl; // line (b)
    cout << x[x[x[2][0]][0]][0] << endl; // line (c)
    up(x,1,1); // line (d)
    cout << up(x,2,1) << endl; // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 103** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int up(int a[][2], int x, int y) {
    if (a[x][y] % 2 == 0) cout << a[x][y] << endl;
    a[x][y]++;
    return a[x][y];
}

int main() {
    int x[3][2] = {{0,1}, {3,4}, {5,7}};
    cout << x[1][1] << endl; // line (a)
    for (int i = 0; i < 2; i++) cout << x[i][i] << endl; // line (b)
    cout << x[x[0][1]][x[0][0]] << endl; // line (c)
    up(x,1,1); // line (d)
    cout << up(x,2,1) << endl; // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 104** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int up(int a[][2], int x, int y) {
    if (y < 1) return a[x][y+1];
    cout << a[x][y] << endl;
    return a[x][y];
}

int main() {
    int x[3][2] = {{2,3},{0,4},{1,5}}, a = 0;
    cout << x[a][a] << endl; // line (a)
    for (int i = 0; i < 2; i++) cout << x[2 - i][i] << endl; // line (b)
    cout << x[x[x[2][0]][0]][0] << endl; // line (c)
    up(x,1,1); // line (d)
    cout << up(x,2,1) << endl; // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 105** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.



```

int main() {
    int a[4] = {314, 159, 265, 358};
    cout << sqrt("FFrreedd") << endl;    // prints: Fred
    cout << firstLetter("Freddy") << endl; // prints: F
    sort(a, 4);                          // prints: 159 265 314 358
    oddElements(a, 4);                   // prints: odd: 159 265
    a[0] = sum(a[1], a[2]);              // adds elements
    return 0;
}

```

(a) Title line for `sqrt`.

**Answer:**

(b) Title line for `firstLetter`.

**Answer:**

(c) Title line for `sort`.

**Answer:**

(d) Title line for `oddElements`.

**Answer:**

(e) Title line for `sum`.

**Answer:**

**Problem 106** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int fun(int &x, int &y) {
    if (y <= 0) return x;
    x = x + 2;
    cout << x << y << endl;
    return x * y;
}

```

```

int main() {
    int x = 5, y = -1;
    cout << fun(x, y) << endl;    // line a
    fun(y, x);                  // line b
    fun(x, y);                  // line c
    fun(y, x);                  // line d
    cout << fun(x, y) << endl;    // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

(a) line a:

(b) line b:

(c) line c:

(d) line d:

(e) line e:

**Problem 107** Write a function called *addThrees* that inserts a 3 after each digit of a positive integer parameter.

For example, a program that uses the function *addThrees* follows.

```
int main() {
    cout << addThrees(3) << endl;      // prints 33
    cout << addThrees(1313) << endl;   // prints 13331333
    cout << addThrees(777) << endl;   // prints 737373
    return 0;
}
```

**Answer:**

**Problem 108** Write a C++ function called *halfs* that divides each element of a 2-dimensional array (with two columns) by 2.

It should be possible to use your function in the following program.

```
main() {
    double data[2][2] = {{1, 2}, {3, 4}};
    halfs (data, 2, 2);
    for (int i = 0; i < 2; i++)
        cout << data[1][i] << " ";    // prints 1.5 2.0
}
```

**Answer:**

**Problem 109** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.

```
int main() {
    int a[4] = {314, 159, 265, 358};
    sqrt("FFreedd");                // prints: Fred
    firstLetter("Freddy");          // prints: F
    printArray(sort(a, 4), 4);      // prints: 159 265 314 358
    cout << oddElements(a, 4);      // prints: odd: 159 265
    swap(a[1], a[2]);              // swaps elements
    return 0;
}
```

(a) Title line for **sqrt**.

**Answer:**

(b) Title line for **firstLetter**.

**Answer:**

(c) Title line for **sort**.

**Answer:**

(d) Title line for **oddElements**.

**Answer:**

(e) Title line for **swap**.

**Answer:**

**Problem 110** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int fun(int &x, int &y) {
    if (y <= 0) return x;
    x = x + 2;
    cout << x << y << endl;
    return x * y;
}

int main() {
    int x = 4, y = 0;
    cout << fun(x, y) << endl;    // line a
    fun(y, x);                    // line b
    fun(x, y);                    // line c
    fun(y, x);                    // line d
    cout << fun(x, y) << endl;    // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

- (a) line a:
- (b) line b:
- (c) line c:
- (d) line d:
- (e) line e:

**Problem 111** Write a function called *addThrees* that inserts a 3 before each digit of a positive integer parameter.

For example, a program that uses the function *addThrees* follows.

```

int main() {
    cout << addThrees(3) << endl;    // prints 33
    cout << addThrees(1313) << endl; // prints 31333133
    cout << addThrees(777) << endl; // prints 373737
    return 0;
}

```

**Answer:**

**Problem 112** Write a C++ function called *roots* that replaces each element of an array by its root.

It should be possible to use your function in the following program.

```

main() {
    double data[3] = {1.0, 4.0, 9.0};
    roots (data, 3);
    for (int i = 0; i < 3; i++)
        cout << data[i] << " ";    // prints 1 2 3
}

```

**Answer:**

**Problem 113** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.

```

int main() {
    int a[4] = {314, 159, 265, 358};
    cout << firstLetter("Freddy") << endl; // prints: F
    cout << sqrt("FFrreedd") << endl;     // prints: Fred
    oddElements(a, 4);                    // prints: odd: 159 265
    sort(a, 4);                            // prints: 159 265 314 358
    a[0] = sum(a[1], a[2]);                // adds elements
    return 0;
}

```

(a) Title line for `firstLetter`.

**Answer:**

(b) Title line for `sqrt`.

**Answer:**

(c) Title line for `oddElements`.

**Answer:**

(d) Title line for `sort`.

**Answer:**

(e) Title line for `sum`.

**Answer:**

**Problem 114** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int fun(int &x, int &y) {
    if (y <= 0) return x;
    x = x + 2;
    cout << x << y << endl;
    return x * y;
}

```

```

int main() {
    int x = 3, y = -1;
    cout << fun(x, y) << endl; // line a
    fun(y, x);                // line b
    fun(x, y);                // line c
    fun(y, x);                // line d
    cout << fun(x, y) << endl; // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

(a) line a:

(b) line b:

(c) line c:

(d) line d:

(e) line e:

**Problem 115** Write a function called `addTwos` that inserts a 2 after each digit of a positive integer parameter.

For example, a program that uses the function `addTwos` follows.

```

int main() {
    cout << addTwos(3) << endl;      // prints 32
    cout << addTwos(1212) << endl;   // prints 12221222
    cout << addTwos(777) << endl;   // prints 727272
    return 0;
}

```

**Answer:**

**Problem 116** Write a C++ function called *squares* that replaces each element of a 2-dimensional array (with two columns) by its square.

It should be possible to use your function in the following program.

```

main() {
    int data[2][2] = {{1, 2}, {3, 4}};
    squares (data, 2, 2);
    for (int i = 0; i < 2; i++)
        cout << data[1][i] << " "; // prints 9 16
}

```

**Answer:**

**Problem 117** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.

```

int main() {
    int a[4] = {314, 159, 265, 358};
    firstLetter("Freddy");           // prints: F
    sqrt("FFreedd");                 // prints: Fred
    cout << oddElements(a, 4);        // prints: odd: 159 265
    printArray(sort(a, 4), 4);       // prints: 159 265 314 358
    swap(a[1], a[2]);                // swaps elements
    return 0;
}

```

(a) Title line for **firstLetter**.

**Answer:**

(b) Title line for **sqrt**.

**Answer:**

(c) Title line for **oddElements**.

**Answer:**

(d) Title line for **sort**.

**Answer:**

(e) Title line for **swap**.

**Answer:**

**Problem 118** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int fun(int &x, int &y) {
    if (y <= 0) return x;
    x = x + 2;
    cout << x << y << endl;
    return x * y;
}

int main() {
    int x = 2, y = 0;
    cout << fun(x, y) << endl;    // line a
    fun(y, x);                   // line b
    fun(x, y);                   // line c
    fun(y, x);                   // line d
    cout << fun(x, y) << endl;    // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

- (a) line a:
- (b) line b:
- (c) line c:
- (d) line d:
- (e) line e:

**Problem 119** Write a function called *addTwos* that inserts a 2 before each digit of a positive integer parameter. For example, a program that uses the function *addTwos* follows.

```

int main() {
    cout << addTwos(3) << endl;    // prints 23
    cout << addTwos(1212) << endl; // prints 21222122
    cout << addTwos(777) << endl; // prints 272727
    return 0;
}

```

**Answer:**

**Problem 120** Write a C++ function called *cubes* that replaces each element of an array by its cube. It should be possible to use your function in the following program.

```

main() {
    int data[3] = {1, 2, 3};
    cubes (data, 3);
    for (int i = 0; i < 3; i++)
        cout << data[i] << " "; // prints 1 8 27
}

```

**Answer:**

**Problem 121** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.

```

int main() {
    string a[4] = {"Freddy", "Max", "Kelly", "Jack"};
    undouble(11223344);           // prints: 1234
    firstDigit(65536);           // prints: Six
    printSorted(a, 4);           // prints: Freddy Jack Kelly Max
    cout << join(a[1], a[3]) << endl; // prints: MaxJack
    randomWords(a, 4);           // assigns new random values to array
    return 0;
}

```

(a) Title line for **undouble**.

**Answer:**

(b) Title line for **firstDigit**.

**Answer:**

(c) Title line for **printSorted**.

**Answer:**

(d) Title line for **join**.

**Answer:**

(e) Title line for **randomWords**.

**Answer:**

**Problem 122** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int fun(int &x, int y) {
    if (y <= 0) return x;
    x = x + 1;
    y = y + 1;
    cout << x << y << endl;
    return x * y;
}

int main() {
    int x = 5, y = -1;
    cout << fun(x, y) << endl; // line a
    fun(x, 1);                // line b
    fun(y, 1);                // line c
    fun(y, x);                // line d
    cout << fun(x, 2) << endl; // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

(a) line a:

(b) line b:

(c) line c:

(d) line d:

(e) line e:

**Problem 123** Write a function called *killTwos* that deletes all digits that are multiples of 2 from a positive integer parameter.

For example, a program that uses the function *killTwos* follows.

```
int main() {
    cout << killTwos(11) << endl;      // prints 11
    cout << killTwos(1212) << endl;    // prints 11
    cout << killTwos(2400) << endl;    // prints 0, because no digits are left
    return 0;
}
```

**Answer:**

**Problem 124** Write a C++ function called *numOdd* that returns the number of odd elements in a 2-dimensional array (with 4 columns).

It should be possible to use your function in the following program. (The output from this program is 2 because only the two 1s are odd).

```
main() {
    int data[2][4] = {{11, 12, 14, 0}, {32, 12, 132, 11}};
    int x;
    x = numOdd (data, 2, 4);
    // data is the 2-d array, 2 and 4 are its capacities
    cout << "The number of odds is: " << x << endl;
}
```

**Answer:**

**Problem 125** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.

```
int main() {
    string a[4] = {"Freddy", "Max", "Kelly", "Jack"};
    cout << undouble(11223344);          // prints: 1234
    cout << firstDigit(65536) << endl;   // prints: Six
    sort(a, 4);                          // prints: Freddy Jack Kelly Max
    cout << halfString(a[0]) << endl;    // prints: Fre
    a[1] = randomWord();                  // assigns a random value
    return 0;
}
```

(a) Title line for **undouble**.

**Answer:**

(b) Title line for **firstDigit**.

**Answer:**

(c) Title line for **sort**.

**Answer:**

(d) Title line for **halfString**.

**Answer:**

(e) Title line for **randomWord**.

**Answer:**

**Problem 126** Consider the following C++ program.



```

#include <iostream>
using namespace std;

int fun(int &x, int y) {
    if (y <= 0) return x;
    x = x + 1;
    y = y + 1;
    cout << x << y << endl;
    return x * y;
}

int main() {
    int x = 4, y = 0;
    cout << fun(x, y) << endl;    // line a
    fun(x, 1);                   // line b
    fun(y, 1);                   // line c
    fun(y, x);                   // line d
    cout << fun(x, 2) << endl;    // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

- (a) line a:
- (b) line b:
- (c) line c:
- (d) line d:
- (e) line e:

**Problem 127** Write a function called *twos* that deletes all digits that are not multiples of 2 from a positive integer parameter.

For example, a program that uses the function *twos* follows.

```

int main() {
    cout << twos(23) << endl;    // prints 2
    cout << twos(1212) << endl;  // prints 22
    cout << twos(777) << endl;   // prints 0, because nothing is left
    return 0;
}

```

**Answer:**

**Problem 128** Write a C++ function called *range* that returns the difference between the largest and smallest elements in a 2-dimensional array (with 4 columns).

It should be possible to use your function in the following program. (The output from this program is 10 because the difference between the largest element 13 and the smallest element 3 is  $13 - 3 = 10$ ).

```

main() {
    int data[2][4] = {{11, 12, 11, 5}, {6, 3, 12, 13}};
    int x;
    x = range (data, 2, 4);
    // data is the 2-d array, 2 and 4 are its capacities
    cout << "The range is: " << x << endl;
}

```

**Answer:**

**Problem 129** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.

```
int main() {
    string a[4] = {"Freddy", "Max", "Kelly", "Jack"};
    firstDigit(65536);           // prints: Six
    undouble(11223344);         // prints: 1234
    cout << join(a[1], a[3]) << endl; // prints: MaxJack
    printSorted(a, 4);          // prints: Freddy Jack Kelly Max
    randomWords(a, 4);          // assigns new random values to array
    return 0;
}
```

(a) Title line for **firstDigit**.

**Answer:**

(b) Title line for **undouble**.

**Answer:**

(c) Title line for **join**.

**Answer:**

(d) Title line for **printSorted**.

**Answer:**

(e) Title line for **randomWords**.

**Answer:**

**Problem 130** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int fun(int &x, int y) {
    if (y <= 0) return x;
    x = x + 1;
    y = y + 1;
    cout << x << y << endl;
    return x * y;
}

int main() {
    int x = 3, y = -1;
    cout << fun(x, y) << endl; // line a
    fun(x, 1);                // line b
    fun(y, 1);                // line c
    fun(y, x);                // line d
    cout << fun(x, 2) << endl; // line e
    return 0;
}
```

What is the output from the program at each of the following lines:

(a) line a:

(b) line b:

(c) line c:

(d) line d:

(e) line e:

**Problem 131** Write a function called *killTwos* that deletes all digits that are equal to 2 from a positive integer parameter.

For example, a program that uses the function *killTwos* follows.

```
int main() {
    cout << killTwos(11) << endl;      // prints 11
    cout << killTwos(1212) << endl;   // prints 11
    cout << killTwos(222) << endl;    // prints 0, because no digits are left
    return 0;
}
```

**Answer:**

**Problem 132** Write a C++ function called *numEven* that returns the number of even elements in a 2-dimensional array (with 3 columns).

It should be possible to use your function in the following program. (The output from this program is 2 because only the two 12s are even).

```
main() {
    int data[2][3] = {{11, 12, 11}, {3, 12, 13}};
    int x;
    x = numEven (data, 2, 3);
    // data is the 2-d array, 2 and 3 are its capacities
    cout << "The number of evens is: " << x << endl;
}
```

**Answer:**

**Problem 133** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.** Your title lines must allow for any indicated types of output.

```
int main() {
    string a[4] = {"Freddy", "Max", "Kelly", "Jack"};
    cout << firstDigit(65536) << endl;    // prints: Six
    cout << undouble(11223344);          // prints: 1234
    cout << halfString(a[0]) << endl;    // prints: Fre
    sort(a, 4);                          // prints: Freddy Jack Kelly Max
    a[1] = randomWord();                  // assigns a random value
    return 0;
}
```

(a) Title line for **firstDigit**.

**Answer:**

(b) Title line for **undouble**.

**Answer:**

(c) Title line for **halfString**.

**Answer:**

(d) Title line for **sort**.

**Answer:**

(e) Title line for **randomWord**.

**Answer:**

**Problem 134** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int fun(int &x, int y) {
    if (y <= 0) return x;
    x = x + 1;
    y = y + 1;
    cout << x << y << endl;
    return x * y;
}

int main() {
    int x = 2, y = 0;
    cout << fun(x, y) << endl;    // line a
    fun(x, 1);                   // line b
    fun(y, 1);                   // line c
    fun(y, x);                   // line d
    cout << fun(x, 2) << endl;    // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

- (a) line a:
- (b) line b:
- (c) line c:
- (d) line d:
- (e) line e:

**Problem 135** Write a function called *twos* that deletes all digits that are not equal to 2 from a positive integer parameter.

For example, a program that uses the function *twos* follows.

```

int main() {
    cout << twos(23) << endl;    // prints 2
    cout << twos(1212) << endl;  // prints 22
    cout << twos(777) << endl;   // prints 0, because nothing is left
    return 0;
}

```

**Answer:**

**Problem 136** Write a C++ function called *range* that returns the difference between the largest and smallest elements in a 2-dimensional array (with 3 columns).

It should be possible to use your function in the following program. (The output from this program is 10 because the difference between the largest element 13 and the smallest element 3 is  $13 - 3 = 10$ ).

```

main() {
    int data[2][3] = {{11, 12, 11}, {3, 12, 13}};
    int x;
    x = range (data, 2, 3);
    // data is the 2-d array, 2 and 3 are its capacities
    cout << "The range is: " << x << endl;
}

```

**Answer:**

**Problem 137** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```
int main() {
    int a[5] = {3,1,4,1,5};
    int x[2][3] = {{0,1,3},{2,4,5}};
    string s= "Hello";
    string t;

    cout << average(a, 5) << endl;           // prints the average:  2.8
    t = reverse(s); cout << t << endl;       // prints:  olleH
    reverseRows(x, 2, 3);                   // prints:  2 4 5, 0 1 3
    if (hasRepeat(a, 5)) cout << "Has repeat" << endl;
                                           // prints:  Has repeat
    t = entries(a, 5); cout << t << endl;    // prints:  3,1,4,1,5
    return 0;
}
```

(a) Title line for **average**

**Answer:**

(b) Title line for **reverse**

**Answer:**

(c) Title line for **reverseRows**

**Answer:**

(d) Title line for **hasRepeat**

**Answer:**

(e) Title line for **entries**

**Answer:**

**Problem 138** Consider the following C++ program.

```
#include <iostream>
using namespace std;

char f(string s, int n) {
    if (n >= s.length()) return 'A';
    return s[n];
}

int mystery (int x) {
    if (x > 5) return 0;
    cout << -x;
    return x;
}

int main () {
    cout << f("Hello", 20) << endl;           //line A
    cout << f("Hello", 1) << endl;           //line B
    cout << mystery(19683) << endl;         //line C
    cout << mystery(2) << endl;            //line D
    mystery(-5);                             //line E
    cout << endl;
    return 0;
}
```

(a) What is the output at line A?

**Answer:**

(b) What is the output at line B?

**Answer:**

(c) What is the output at line C?

**Answer:**

(d) What is the output at line D?

**Answer:**

(e) What is the output at line E?

**Answer:**

**Problem 139** Write a function called *extraOne* that places an initial 1 at the start of an integer parameter. (Assume that the input parameter is not negative.)

For example, a program that uses the function *extraOne* follows.

```
int main() {
    int x = extraOne(729);
    cout << x << endl;    // prints    1729
    return 0;
}
```

**Answer:**

**Problem 140** Write a function called *dropDimension* that copies the entries from a 2-dimensional array row by row as the entries of a 1-dimensional array. Assume that the 1-dimensional array has more than enough capacity for these entries. (The function should use capacities of the 2-dimensional array but not the 1-dimensional array as input parameters.)

For example, a program that uses the function follows.

```
int main() {
    int x[100];
    int y[2][3] = {{3,1,4}, {1,5,9}};
    int yrows = 2, ycols = 3;
    dropDimension(y, yrows, ycols, x);
    for (int i = 0; i <= 5; i++) cout << x[i];
    // 314159    is printed
    cout << endl;
    return 0;
}
```

**Answer:**

**Problem 141** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**



(a) What is the output at line A?

**Answer:**

(b) What is the output at line B?

**Answer:**

(c) What is the output at line C?

**Answer:**

(d) What is the output at line D?

**Answer:**

(e) What is the output at line E?

**Answer:**

**Problem 143** Write a function called *doubleEight* that places an extra digit 8 after the last 8 in an integer parameter. If there is no 8 present, nothing is done. (Assume that the input parameter is not negative.)

For example, a program that uses the function *doubleEight* follows.

```
int main() {
    int x = doubleEight(19683);
    cout << x << endl;           // prints 196883
    cout << doubleEight(271828) << endl; // prints 2718288
    cout << doubleEight(314159) << endl; // prints 314159
    return 0;
}
```

**Answer:**

**Problem 144** Write a function called *dropDimension* that copies the entries from a 2-dimensional array column by column as the entries of a 1-dimensional array. Assume that the 1-dimensional array has more than enough capacity for these entries. (The function should use capacities of the 2-dimensional array but not the 1-dimensional array as input parameters.)

For example, a program that uses the function follows.

```
int main() {
    int x[100];
    int y[2][3] = {{3,4,5}, {1,1,9}};
    int yrows = 2, ycols = 3;
    dropDimension(y, yrows, ycols, x);
    for (int i = 0; i <= 5; i++) cout << x[i];
    // 314159 is printed
    cout << endl;
    return 0;
}
```

**Answer:**

**Problem 145** Write a function called *extraTwo* that inserts an extra digit 2 as the second digit of an integer parameter. (Assume that the input parameter is positive.)

For example, a program that uses the function *extraTwo* follows.



```

int main() {
    int x = extraTwo(79);
    cout << x << endl;           // prints 729
    cout << extraTwo(1) << endl; // prints 12
    return 0;
}

```

**Answer:**

**Problem 146** Write a function called *fill2D* that fills the entries of a 2-dimensional array column by column from the entries of a 1-dimensional array. Assume that the 1-dimensional array has more than enough capacity for these entries. (The function should use capacities of the 2-dimensional array but not the 1-dimensional array as input parameters.)

For example, a program that uses the function follows.

```

int main() {
    int x[11] = {3,1,4,1,5,9,2,6,5,3,5};
    int y[2][3];
    int yrows = 2, ycols = 3;
    fill2D(y, yrows, ycols, x);
    for (int i = 0; i < yrows; i++) {
        for (int j = 0; j < ycols; j++) cout << y[i][j];
        cout << endl;
    }
    // 345 is printed
    // 119
    return 0;
}

```

**Answer:**

**Problem 147** Write a function called *doubleFour* that places an extra copy of the 4th digit right after that digit in an integer parameter. If there is no 4th digit, nothing is done. (Assume that the input parameter is not negative.)

For example, a program that uses the function *doubleFour* follows.

```

int main() {
    int x = doubleFour(19683);
    cout << x << endl;           // prints 196883
    cout << doubleFour(271828); // prints 2718828
    cout << doubleFour(314159); // prints 3141159
    return 0;
}

```

**Answer:**

**Problem 148** Write a function called *fill2D* that fills the entries of a 2-dimensional array row by row from the entries of a 1-dimensional array. Assume that the 1-dimensional array has more than enough capacity for these entries. (The function should use capacities of the 2-dimensional array but not the 1-dimensional array as input parameters.)

For example, a program that uses the function follows.

```

int main() {
    int x[11] = {3,1,4,1,5,9,2,6,5,3,5};
    int y[2][3];
    int yrows = 2, ycols = 3;
}

```

```

fill2D(y, yrows, ycols, x);
for (int i = 0; i < yrows; i++) {
    for (int j = 0; j < ycols; j++) cout << y[i][j];
    cout << endl;
}
// 314 is printed
// 159
return 0;
}

```

**Answer:**

**Problem 149** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {

    int i = 3, j = 5;
    int a[9] = {3,1,4,1,5,9,2,6,5};
    int x[3][2] = {{0,1},{3,2},{4,5}};

    cout << min(i, j) << endl;           // prints minimum
    printArray(x, 3, 2);                // prints array
    cout << average(a, 9) << endl;      // prints average
    swap(a, 3, 5);                      // swap elements 3 and 5
    reverse(a[1]);                      // reverse the digits in a[1]
    return 0;
}

```

(a) Title line for **min**

**Answer:**

(b) Title line for **printArray**

**Answer:**

(c) Title line for **average**

**Answer:**

(d) Title line for **swap**

**Answer:**

(e) Title line for **reverse**

**Answer:**

**Problem 150** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int recursive (int n) {
    if (n < 10) return n;
    return 100 * recursive (n / 100) + 10 * (n % 10);
}

int mystery (int x) {
    cout << x << "54321";
    return x;
}

int main () {
    cout << recursive (7) << endl;      //line A
    cout << recursive (135) << endl;    //line B
    cout << recursive (19683) << endl;  //line C
    cout << mystery (2) << endl;       //line D
    mystery (2);                        //line E
    return 0;
}

```

(a) What is the output at line A?

**Answer:**

(b) What is the output at line B?

**Answer:**

(c) What is the output at line C?

**Answer:**

(d) What is the output at line D?

**Answer:**

(e) What is the output at line E?

**Answer:**

**Problem 151** Write a function called *smallestDigit* that finds the smallest digit in an integer parameter. (Assume that the input parameter is not negative.)

For example, a program that uses the function *smallestDigit* follows.

```

int main() {
    cout << smallestDigit(29) << endl;    // prints    2
    cout << smallestDigit(31415) << endl; // prints    1
    cout << smallestDigit(7) << endl;     // prints    7
    return 0;
}

```

**Answer:**

**Problem 152** Write a function called *lastIndex* that finds the largest index of an entry in an array of integers that matches a given target. If the target is not present the function should return an answer of  $-1$ .

For example, a program that uses the function follows.

```

int main() {
    int x[6] = {3, 1, 4, 1, 5, 9};
    int capacity = 6;
    int target = 5;
    cout << lastIndex(x, capacity, target) << endl;
    // prints 4 because the target 5 is found as element number 4
    cout << lastIndex(x, capacity, 1) << endl;
    // prints 3 because the target 1 is last found as element number 3
    cout << lastIndex(x, capacity, 8) << endl;
    // prints -1 because the target 8 is not found.
    return 0;
}

```

**Answer:**

**Problem 153** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {

    int i = 3, j = 5;
    int a[9] = {3,1,4,1,5,9,2,6,5};
    int x[3][2] = {{0,1},{3,2},{4,5}};

    cout << average(i, j) << endl;           // prints average
    printArray(a, 9);                       // prints array
    cout << min(x, 3, 2) << endl;           // prints minimal element
    reverse(a, 9);                          // reverse the order of elements
    swap(a[1], a[2]);                        // swap two values
    return 0;
}

```

(a) Title line for **average**

**Answer:**

(b) Title line for **printArray**

**Answer:**

(c) Title line for **min**

**Answer:**

(d) Title line for **reverse**

**Answer:**

(e) Title line for **swap**

**Answer:**

**Problem 154** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int recursive (int n) {
    if (n < 10) return n;
    return 100 * recursive (n / 100) + 11 * (n % 10);
}

int mystery (int x) {
    cout << x << "12345";
    return x;
}

int main () {
    cout << recursive (7) << endl;      //line A
    cout << recursive (135) << endl;    //line B
    cout << recursive (19683) << endl; //line C
    cout << mystery (2) << endl;      //line D
    mystery (2);                       //line E
    return 0;
}

```

(a) What is the output at line A?

**Answer:**

(b) What is the output at line B?

**Answer:**

(c) What is the output at line C?

**Answer:**

(d) What is the output at line D?

**Answer:**

(e) What is the output at line E?

**Answer:**

**Problem 155** Write a function called *biggestDigit* that finds the biggest digit in an integer parameter. (Assume that the input parameter is not negative.)

For example, a program that uses the function *biggestDigit* follows.

```

int main() {
    cout << biggestDigit(29) << endl;    // prints 9
    cout << biggestDigit(31415) << endl; // prints 5
    cout << biggestDigit(7) << endl;    // prints 7
    return 0;
}

```

**Answer:**

**Problem 156** Write a function called *firstIndex* that finds the smallest index of an entry in an array of integers that matches a given target. If the target is not present the function should return an answer of  $-1$ .

For example, a program that uses the function follows.

```

int main() {
    int x[6] = {3, 1, 4, 1, 5, 9};
    int capacity = 6;
    int target = 5;
    cout << firstIndex(x, capacity, target) << endl;
    // prints 4 because the target 5 is found as element number 4
    cout << firstIndex(x, capacity, 1) << endl;
    // prints 1 because the target 1 is first found as element number 1
    cout << firstIndex(x, capacity, 8) << endl;
    // prints -1 because the target 8 is not found.
    return 0;
}

```

**Answer:**

**Problem 157** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {

    int a[4] = {3,1,4,1}, i = 3, j = 5, k = 4;
    int b[4] = {2,7,1,8};
    int x[2][2] = {{0,1},{3,2}};

    cout << max(i, j, k) << endl;           // prints maximum
    printMax(a, 4);                       // prints maximum
    cout << max2d(x, 2, 2) << endl;       // prints maximum
    swap(i, j);                            // swap
    swapArrays(a, b, 4);                  // swap first 4 elements in arrays
    return 0;
}

```

(a) Title line for **max**

**Answer:**

(b) Title line for **printMax**

**Answer:**

(c) Title line for **max2d**

**Answer:**

(d) Title line for **swap**

**Answer:**

(e) Title line for **swapArrays**

**Answer:**

**Problem 158** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int main() {
    int x;
    cout << "Enter an integer:";
    cin >> x;

    if (x > 0) cout << "Goodbye" << endl;
    if (x < -10) {
        cout << x + 2 << endl;
        return 0;
    }
    else if (x % 2 != 0) cout << "odd" << endl;

    for (int i = 1; i < x; i++) cout << i;
    cout << endl;
    for (int i = 1; i <= -x; i++) {
        for (int j = 1; j <= 3; j++) cout << "*";
        cout << endl;
    }

    return 0;
}

```

(a) What is the output if the user enters *-729*?

**Answer:**

(b) What is the output if the user enters *4*?

**Answer:**

(c) What is the output if the user enters *-5*?

**Answer:**

(d) What is the output if the user enters *-4*?

**Answer:**

(e) What is the output if the user enters *3*?

**Answer:**

**Problem 159** Write a function called *doubleFirst* that places an extra copy of the first digit at the start of a number.

For example, a program that uses the function *doubleFirst* follows.

```

int main() {
    cout << doubleFirst(29) << endl;    // prints    229
    cout << doubleFirst(19683) << endl; // prints 119683
    cout << doubleFirst(9) << endl;    // prints    99
    return 0;
}

```

**Answer:**

**Problem 160** Write a function called *findLargest* that finds the largest possibility for the sum of the entries in a row of a 2-dimensional array of integers. The array and the capacities are parameters.

For example, a program that uses the function follows.

```

int main() {
    int d[2][3] = {{2,4,6}, {1,3,5}};
    cout << findLargest(d, 2, 3) << endl;
    // prints    12, because the sum 12 = 2+4+6 is larger than 1+3+5
    return 0;
}

```

**Answer:**

**Problem 161** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {

    int a[4] = {3,1,4,1}, i = 3, j = 5, k = 4;
    int x[2][2] = {{0,1},{3,2}};

    cout << average(i, j, k) << endl;           // prints average
    printAverage(a, 4);                       // prints average
    cout << average2d(x, 2, 2) << endl;        // prints average
    sort(i, j ,k );                          // sort into order
    sort3(a, 4);                             // sort into order
    return 0;
}

```

(a) Title line for **average**

**Answer:**

(b) Title line for **printAverage**

**Answer:**

(c) Title line for **average2d**

**Answer:**

(d) Title line for **sort**

**Answer:**

(e) Title line for **sort3**

**Answer:**

**Problem 162** Consider the following C++ program.



```

#include <iostream>
using namespace std;

int main() {
    int x;
    cout << "Enter an integer:";
    cin >> x;

    if (x < 0) cout << "Goodbye" << endl;
    if (x > 10) {
        cout << x % 10 << endl;
        return 0;
    }
    else if (x % 2 != 0) cout << "odd" << endl;

    for (int i = 1; i <= x; i++) cout << i;
    cout << endl;
    for (int i = 1; i < -x; i++) {
        for (int j = 1; j < 3; j++) cout << "*";
        cout << endl;
    }

    return 0;
}

```

(a) What is the output if the user enters *729*?

**Answer:**

(b) What is the output if the user enters *9*?

**Answer:**

(c) What is the output if the user enters *5*?

**Answer:**

(d) What is the output if the user enters *4*?

**Answer:**

(e) What is the output if the user enters *-3*?

**Answer:**

**Problem 163** Write a function called *dropSecond* that removes the second digit of an integer parameter. (Assume that the input parameter is not negative. If the parameter has just one digit, return that digit.)

For example, a program that uses the function *dropSecond* follows.

```

int main() {
    cout << dropSecond(29) << endl;    // prints 2, the 9 dropped
    cout << dropSecond(19683) << endl; // prints 1683, the 9 dropped
    cout << dropSecond(9) << endl;    // prints 9
    return 0;
}

```

**Answer:**

**Problem 164** Write a function called *findLargest* that finds the largest entry in a specified column of a 2-dimensional array of integers. The array, the capacities, and the specified column are parameters.

For example, a program that uses the function follows.

```

int main() {
    int d[2][3] = {{2,4,6}, {1,3,5}};
    cout << findLargest(d, 2, 3, 0) << endl;
    // prints    2, because this is the largest entry in column 0
    return 0;
}

```

**Answer:**

**Problem 165** Write title lines (header lines or prototypes) for the following functions. Do not supply the blocks for the functions.

(a) A function called **num7s** which returns the number of digits equal to 7 in an input integer.

**Answer:**

(b) A function called **num7s** which returns the number of elements equal to 7 in an input array of integers.

**Answer:**

(c) A function called **num7s** which returns the number of characters equal to 7 in an input string.

**Answer:**

(d) A function called **num7s** which changes an integer parameter to be the number of 7's in its decimal expansion. (For example if the input is 777111 it would be changed to 3 because it has 3 digits equal to 7.)

**Answer:**

(e) A function called **num7s** which returns the number of elements equal to 7 in a 2-dimensional array of integers with size  $7 \times 7$ .

**Answer:**

**Problem 166** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int fun(int x) {
    if (x <= 0) return 0;
    if (x >= 9 && x % 2 == 1) return x - 1;
    if (x >= 9 || x % 3 == 0) return x - 2;
    return 7;
}

int rec(int x) {
    if (x < 10) return fun(x);
    return rec(x / 10) + rec(x % 10);
}

int main() {
    cout << fun(3) << endl;    // line (a)
    cout << fun(30) << endl;   // line (b)
    cout << fun(33) << endl;   // line (c)
    cout << rec(33) << endl;   // line (d)
    cout << rec(999) << endl;  // line (e)
}

```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 167** Write a function called *startBinary* that returns a number giving the first 2 digits in the binary expansion of an integer parameter. (Assume that the input parameter is not negative. If the parameter has just one binary digit, return that digit.)

For example, a program that uses the function *startBinary* follows.

```
int main() {
    int x = startBinary(6);
    cout << x << endl;           // prints 11 because 6 in binary is 110
    cout << startBinary(23) << endl; // prints 10 because 23 is 10111 in binary
    cout << startBinary( 3) << endl; // prints 11 because  3 is   11 in binary
    cout << startBinary( 1) << endl; // prints  1 because  1 is   1 in binary
    return 0;
}
```

**Answer:**

**Problem 168** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

The program asks the user to enter a positive integer  $n$  that is less than 100. If the user enters an incorrect value, the program terminates. The program next asks the user to enter  $n^2$  strings to be stored in a 2-dimensional array with size  $n \times n$ . The program then reports the maximum number of times that it can find the string *Kamil* in any row or column of the array.

For example, if the user enters 4 for  $n$  and then enters the 16 strings:

```
Kamil Peter  Dustin Kamil
Kamil Andrew Carl  Phil
Rat  Rat    Rat    Rat
Kamil Peter  Dustin Kamil
```

The final output would be 3 because Kamil appears three times in the first column, and no more than three times in any row or column.

**Answer:**

**Problem 169** Write header lines (prototypes) for the following functions. **Do not attempt to supply the blocks for the functions.**

(a) A function called **isNegative** that tests whether a decimal number is negative.

**Answer:**

(b) A function called **thirdChar** which uses a string as input and returns the third character in the string.

**Answer:**

(c) A function called **swapLast2** which modifies an array of integers. The task of the function is to swap the last two elements of the array.

**Answer:**

(d) A function called **printPic** which uses as input an  $6 \times 6$  array of characters that represents a picture. The task of the function is to print the picture.

**Answer:**

(e) A function called **reverseArray** which is to reverse the order of elements in an array of integers.

**Answer:**

**Problem 170** Consider the following C++ program.

```
#include <iostream>
using namespace std;

void mystery(int data[], int p, int q) {
    data[p] = data[q];
    data[q] = data[p];
}

void m2(int &p, int q) {
    int temp = p;
    p = q;
    q = temp;
}

void print(int data[], int p) {
    for (int i = 0; i < p; i++)
        cout << data[i] << " ";
    cout << endl;
}

main() {
    int x[8] = {0, 1, 2, 3, 4, 5, 6, 7};
    int y[7] = {0, 1, 2, 3, 4, 5, 6};
    int a = 3, b = 4;

    print(x, 3);                // line (a)
    mystery(x, 1, 2); print(x, 5); // line (b)
    for (int i = 1; i <= 7; i++) mystery(x, 0, i);
    print(x, 8);                // line (c)
    m2(a, b);    cout << a << b << endl; // line (d)
    m2(y[3], 7);    print(y, 6);    // line (e)
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 171** Write a function called *doubleDigit* that makes each digit of an input parameter repeat twice.

For example, a program that uses the function *doubleDigit* follows.

```
int main() {
    cout << doubleDigit(9) << endl;           // prints 99
    cout << doubleDigit(81) << endl;          // prints 8811
    cout << doubleDigit(243) << endl;         // prints 224433
    cout << doubleDigit(244) << endl;         // prints 224444
    return 0;
}
```

**Answer:**

**Problem 172** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

The program asks the user to enter 1000 single digit integers. It then outputs the digit or digits that appears least often.

For example, if the user enters 3, 1, 4, 1, 5, 9, . . . , 9, 8 where 0 appears 93 times, 1 appears 116 times, 2 appears 103 times, 3 appears 103 times, 4 appears 93 times, 5 appears 97 times, 6 appears 94 times, 7 appears 95 times, 8 appears 101 times, 9 appears 105 times the output would be:

The digits 0 and 4 are least frequent.

**Answer:**

**Problem 173** Write title lines (header lines or prototypes) for the following functions. Do not supply the blocks for the functions.

(a) A function called **detectAge** which returns a user's age (by asking for input and rejecting negative values).

**Answer:**

(b) A function called **sortString** that sorts an array of strings into alphabetical order.

**Answer:**

(c) A function called **sort4** that sorts 4 integer parameters into increasing order.

**Answer:**

(d) A function called **printCode** that prints the ASCII code for a character.

**Answer:**

(e) A function called **delete7** which alters an integer parameter by deleting every occurrence of the digit 7.

**Answer:**

**Problem 174** Consider the following C++ program.

```
#include <iostream>
using namespace std;

void mystery(int x[][4], int a, int b, int k) {
    for (int r = a; r <= b; r++) for (int c = a; c <= b; c++)
        x[r][c] = k;
}

void print(int x[][4], int s) {
    for (int r = 0; r < s; r++) {
        for (int c = 0; c < s; c++) cout << x[r][c];
        cout << endl;
    }
    cout << endl;
}

int main() {
    int x[4][4] = {{0,0,0,0}, {0,0,0,0}, {0,0,0,0}, {0,0,0,0}};
    mystery(x, 3, 2, 1); print(x, 4); // line (a)
    mystery(x, 0, 1, 2); print(x, 4); // line (b)
    mystery(x, 1, 2, 3); print(x, 4); // line (c)
    mystery(x, 1, 3, 4); print(x, 4); // line (d)
    mystery(x, 0, 3, 5); print(x, 2); // line (e)
    return 0;
}
```

(a) What is the output at line (a)?

**Answer:**

(b) What is the output at line (b)?

**Answer:**

(c) What is the output at line (c)?

**Answer:**

(d) What is the output at line (d)?

**Answer:**

(e) What is the output at line (e)?

**Answer:**

**Problem 175** Write a function called *cutNine* that prints the part of a number that follows its last 9 digit. (If there is no 9 digit, the whole number is printed. If the last digit is a 9, nothing is printed.)

For example, a program that uses the function *cutNine* follows.

```
int main() {
    cutNine(770);           cout << endl;           // prints 770
    cutNine(135792468);    cout << endl;           // prints 2468
    cutNine(1991991);      cout << endl;           // prints 1
    cutNine(1991999);      cout << endl;           // prints
    return 0;
}
```

**Answer:**

**Problem 176** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

The program asks the user to enter 1000 single digit integers. It then outputs the number of times that each digit was seen.

For example, if the user enters 3,1,4,1,5,9,...,9,8 where 0 appears 93 times, 1 appears 116 times, ..., 9 appears 105 times, the output would be:

```
0 count 93, 1 count 116, 2 count 103, 3 count 103, 4 count 93,  
5 count 97, 6 count 94, 7 count 95, 8 count 101, 9 count 105.
```

**Answer:**

**Problem 177** Write title lines (header lines or prototypes) for the following functions. Do not supply the blocks for the functions.

(a) A function called **add3** which returns the sum of three double parameters.

**Answer:**

(b) A function called **reverseIt** that returns the number obtained by reversing the digits in an integer parameter.

**Answer:**

(c) A function called **randomArray** that sets the values in an array of doubles to have random values.

**Answer:**

(d) A function called **add5** that adds 5 to every entry in a 2-dimensional array each of whose rows has 35 columns.

**Answer:**

(e) A function called **deleteX** which alters a string parameter by deleting every occurrence of the letter X.

**Answer:**

**Problem 178** Consider the following C++ program.

```
#include <iostream>  
using namespace std;  
  
string fun(string x[], int y) {  
    if (y <= 0) return x[1];  
    if (y == 1) return x[0] + x[2];  
    if (y == 2) return "illegal";  
    if (y <= 4) return " 4";  
    return "X" + fun(x, y - 6);  
}  
  
int main() {  
    string array[3] = { "1", "2", "3"};  
    cout << fun(array,0) << endl;           // line a  
    cout << fun(array,1) << endl;           // line b  
    cout << fun(array,2) << endl;           // line c  
    cout << fun(array,4) << endl;           // line d  
    cout << fun(array,12) << endl;         // line e  
    return 0;  
}
```

What is the output from the program at each of the following lines:

(a) line a:

(b) line b:

(c) line c:

(d) line d:

(e) line e:

**Problem 179** Write a function called *makeOne* that returns the result of turning every odd valued digit in an integer parameter to a 1.

For example, a program that uses the function *makeOne* follows.

```
int main() {
    cout << makeOne(770) << endl;    // prints 110
    cout << makeOne(13579) << endl;  // prints 11111
    cout << makeOne(1000) << endl;   // prints 1000
    return 0;
}
```

**Answer:**

**Problem 180** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

The program asks the user to enter 3 positive integers. It then outputs the least frequently encountered digit or digits in those 3 numbers.

For example, if the user enters the integers 123, 45678, and 200 the program should output 9 which occurs less often than any other digit in these numbers.

**Answer:**

**Problem 181** Write title lines (header lines or prototypes) for the following functions. Do not supply the blocks for the functions.

(a) A function called **add3** which returns the sum of three integer parameters.

**Answer:**

(b) A function called **reverseString** that returns the reverse of a string.

**Answer:**

(c) A function called **randomArray** that sets the values in an array of integers to have random values.

**Answer:**

(d) A function called **add3** that adds 3 to every entry in a 2-dimensional array each of whose rows has 25 columns.

**Answer:**

(e) A function called **deleteX** which alters a string parameter by deleting every occurrence of the letter X.

**Answer:**

**Problem 182** Consider the following C++ program.



```

#include <iostream>
using namespace std;

string fun(string x[], int y) {
    if (y <= 0) return x[0];
    if (y == 1) return x[1] + x[2];
    if (y == 2) return "illegal";
    if (y <= 4) return " <= 4";
    return "X" + fun(x, y - 5);
}

int main() {
    string array[3] = { "1", "2", "3"};
    cout << fun(array,0) << endl;           // line a
    cout << fun(array,1) << endl;           // line b
    cout << fun(array,2) << endl;           // line c
    cout << fun(array,4) << endl;           // line d
    cout << fun(array,12) << endl;          // line e
    return 0;
}

```

What is the output from the program at each of the following lines:

- (a) line a:
- (b) line b:
- (c) line c:
- (d) line d:
- (e) line e:

**Problem 183** Write a function called *makeOne* that returns the result of turning every non-zero digit in an integer parameter to a 1.

For example, a program that uses the function *makeOne* follows.

```

int main() {
    cout << makeOne(770) << endl;           // prints 110
    cout << makeOne(13579) << endl;          // prints 11111
    cout << makeOne(1000) << endl;          // prints 1000
    return 0;
}

```

**Answer:**

**Problem 184** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

The program asks the user to enter 3 positive integers. It then outputs the most frequently encountered digit or digits in those 3 numbers.

For example, if the user enters the integers 737, 13579, and 246 the program should output 7 which occurs more often than any other digit in these numbers.

**Answer:**

**Problem 185** Write **title lines** for the functions that are called by the following main program. **Do not supply the blocks for the functions.**

```

int main() {
    int a[4] = {3,1,4,1}, b[5] = {2,7,1,8,1}, i = 3, j = 5, k = 4;
    int x[2][2] = {{0,1},{3,2}};
    cout << max(x, 2, 2); // outputs: 3
    printArray(a, 4); // outputs: 3,1,4,1
    reverse(a, 0, 3); // changes a to 1,4,1,3
    sort1(b, 5);
    printArray(b, 5); // outputs: 1,1,2,7,8
    sort2(i, j, k);
    cout << i << j << k << endl; // outputs: 345
    return 0;
}

```

(a) Title line for **max**

**Answer:**

(b) Title line for **printArray**

**Answer:**

(c) Title line for **reverse**

**Answer:**

(d) Title line for **sort1**

**Answer:**

(e) Title line for **sort2**

**Answer:**

**Problem 186** Consider the following C++ program.

```

#include <iostream>
using namespace std;

void rec(int a[], int start, int stop) {
    if (stop <= start) return;
    a[start] = a[stop];
    rec(a, start + 1, stop -1);
}

void printA(int a[], int cap) {
    for (int c = cap - 1; c >= 0; c--) cout << a[c] << " ";
    cout << endl;
}

int main() {
    int x[6] = {0, 1, 2, 3, 4, 5};

    printA(x, 6); // line (a)
    printA(x, 4); // line (b)
    rec(x, 3, 3); printA(x, 4); // line (c)
    rec(x, 3, 4); printA(x, 6); // line (d)
    rec(x, 0, 5); printA(x, 6); // line (e)

    return 0;
}

```

What is the output at each of the following lines?

- (a) line (a)
- (b) line (b)
- (c) line (c)
- (d) line (d)
- (e) line (e)

**Problem 187** Write a function called *maxMid* that determines the maximum value in the middle column of a 2-dimensional array of numbers of type double. (You should assume that the 2-dimensional array has an odd number of columns.)

For example, a program that uses the function *maxMid* follows. Your function must complete this program.

```
int main() {
    double x[4][5] = {{0,1,2,3,4}, {1,2,3,4,5}, {2,3,4,5,6}, {5,6,7,8,9}};
    cout << maxMid(x, 4, 5) << endl; // prints 7.0
    return 0;
}
```

**Answer:**

**Problem 188** Write a complete C++ program that does the following. (In your program, you do not need to check whether the user enters legal input.)

1. It asks the user to enter a positive integer  $n$  that is at most 100.
2. The program reads  $n$  single digit integers entered by the user. (A single digit integer is an integer  $n$  with  $0 \leq n \leq 9$ .)
3. The program prints a list of all single digit integers that were not entered at all by the user.

For example, the following represents one run of the program.

```
Enter a positive integer (at most 100):    11
Enter 11 single digit integers:
1 1 7 3 3 2 0 3 7 7 7
The following were not entered: 4 5 6 8 9
```

**Answer:**

**Problem 189** Write title lines (header lines or prototypes) for the following functions. Do not supply the blocks for the functions.

- (a) A function called **welcome** which prints the word "Hello" to the screen.

**Answer:**

- (b) A function called **addTwo** that adds 2 to every entry in an array of integers.

**Answer:**

- (c) A function called **randomTruth** which determines and returns a random true/false result.

**Answer:**

- (d) A function called **numberPrimes** which returns the number of prime numbers that lie between a specified pair of input values.

**Answer:**

- (e) A function called **biggerAverage** which determines which of two arrays of integers has the bigger average. It should return the value of this bigger average.

**Answer:**

**Problem 190** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int fun(int &x, int y) {
    x = y + 1;
    y = x + 1;
    cout << x << y << endl;
    return x * y;
}

int main() {
    int x = 2, y = 0;
    fun(x, 8);           // line a
    fun(x, y);          // line b
    fun(y, x);          // line c
    fun(y, x);          // line d
    cout << fun(x, 3) << endl; // line e
    return 0;
}
```

What is the output from the program at each of the following lines:

(a) line a:

(b) line b:

(c) line c:

(d) line d:

(e) line e:

**Problem 191** Write a function called *alternates* that prints every second digit of an integer parameter, starting from the right.

For example, a program that uses the function *alternates* follows.

```
int main() {
    alternates(10); cout << endl; // prints 0
    alternates(123456); cout << endl; // prints 642
    alternates(1000); cout << endl; // prints 00
    return 0;
}
```

**Answer:**

**Problem 192** Write a complete C++ program that does the following. (Programs that correctly carry out some of the tasks will receive partial credit.)

1. It asks the user to enter a positive integer that is between 1 and 26.
2. The program reads a value  $n$  entered by the user. If the value is not legal, the program exits.
3. The program prints an  $n \times n$  pattern of characters, in which the top left character is an 'A'. The top left  $2 \times 2$  block is completed by three 'B' characters. The top left  $3 \times 3$  block is completed by five 'C' characters, and so on. For example, if the user enters 5 for  $n$  the program should print the following picture.

ABCDE  
BBCDE  
CCCDE  
DDDDE  
EEEE

**Answer:**

**Problem 193** Write title lines (header lines or prototypes) for the following functions. Do not supply the blocks for the functions.

(a) A function called **firstDigit** which returns the first digit of an integer.

**Answer:**

(b) A function called **sqrt** that returns the square root of a double precision parameter.

**Answer:**

(c) A function called **oddString** which returns a string made up of the characters in odd position of an input string.

**Answer:**

(d) A function called **randomWord** which is to create and return a random word.

**Answer:**

(e) A function called **sort** which is to sort an array of strings into alphabetical order.

**Answer:**

**Problem 194** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int recursive(int n) {
    if (n < 10) return n;
    if (n < 100) return n/10;
    return 10 * recursive(n / 100) + n % 10;
}

main() {
    int x;
    cout << "Enter an integer: ";
    cin >> x;
    cout << recursive(x) << endl;
    return 0;
}
```

What is the output from the program in response to the following user inputs.

(a) The user enters 5 for x.

(b) The user enters 16 for x.

(c) The user enters 123 for x.

(d) The user enters 1234 for x.

(e) The user enters 19683 for x.

**Problem 195** Write a function called *evens* that deletes all odd digits from a positive integer parameter.

For example, a program that uses the function *evens* follows.

```

int main() {
    cout << evens(16) << endl;      // prints 6
    cout << evens(666) << endl;    // prints 666
    cout << evens(777) << endl;    // prints 0
    return 0;
}

```

**Answer:**

**Problem 196** Write a complete C++ program that does the following.

1. It asks the user to enter a positive integer  $n$  that is at most 100.
2. The program reads in a 2-dimensional array with  $n$  rows and  $n$  columns of integers entered by the user.
3. The program prints out the average of the entries for each column of the array.

For example, the following represents one run of the program.

```

Enter a positive integer (at most 100):    3
Enter 3 rows of 3 integers:
 3 -1  4
10 30 -100
 2 -2  99
The averages of the 3 columns are: 5.0 9.0 1.0

```

**Answer:**

**Problem 197** Write C++ statements to carry out the following tasks. **Do not write complete programs**, just give a single line, or a few lines of C++ instructions. Include declarations for any variable that you use.

- (i) Print the remainder when 101 is divided by 17 to the file *out.txt*.
- (ii) Print a random lower case letter to the screen. (The random letter should be determined by using an appropriate C++ function.)
- (iii) Read a line of text from the user and print the word *Yes* if it contains the character 7.
- (iv) Print the middle character of the string  $s$ . Assume that the string has odd length.
- (v) Swap the values of integer variables called  $x$  and  $y$ .

**Problem 198** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int recursive(int n) {
    if (n < 10) return n;
    return 100 * recursive(n / 100) + 11* (n % 10);
}

main() {
    int x;
    cout << "Enter an integer: ";
    cin >> x;
    cout << recursive(x) << endl;
    return 0;
}

```

What is the output from the program in response to the following user inputs.

- (a) The user enters 5 for  $x$ .
- (b) The user enters -10 for  $x$ .
- (c) The user enters 65 for  $x$ .
- (d) The user enters 123 for  $x$ .
- (e) The user enters 19683 for  $x$ .

**Problem 199** Write a function called *twoPart* that returns the largest power of 2 that divides a positive integer parameter.

For example, a program that uses the function *twoPart* follows.

```
int main() {
    cout << twoPart(16) << endl;    // prints 16
    cout << twoPart(666) << endl;   // prints 2
    cout << twoPart(777) << endl;   // prints 1
    return 0;
}
```

**Answer:**

**Problem 200** Write a complete C++ program that does the following.

1. It asks the user to enter a positive integer  $n$  that is at most 100.
2. The program reads in a 2-dimensional array with  $n$  rows and  $n$  columns of integers entered by the user.
3. The program prints out the maximum entry found for each row of the array.

For example, the following represents one run of the program.

```
Enter a positive integer (at most 100):    3
Enter 3 rows of 3 integers:
3 -1 4
10 30 -100
0 0 0
The maximum entries in the 3 rows are: 4 30 0
```

**Answer:**

**Problem 201** Write C++ statements to carry out the following tasks. **Do not write complete programs**, just give a single line, or a few lines of C++ instructions. Assume that the following variables have been declared, and if necessary have values, for each part:

```
int x[10], z[10][10], r, c;
string s;
```

- (i) Print the remainder when  $r$  is divided by  $c$ .
- (ii) Set  $r$  to be a random integer between 1 and 10. (The random integer should be determined by an appropriate C++ function.)
- (iii) Print the sum of all 10 entries of the array  $x$ .
- (iv) Print the last character of the string  $s$ .
- (v) Swap row number 0 with row number 4 in the 2-dimensional array  $z$ .

**Problem 202** Consider the following C++ program.

```

#include <iostream>
using namespace std;

void x1(int a[][6], int n) {
    for (int i = 0; i < 5; i++) cout << a[n][i];
    cout << endl;
}

void x2(int b[][6], int n) {
    for (int i = 0; i < n; i++)
        cout << b[i][i] << " ";
    x1(b, n);
}

main() {
    int x[6][6], a[6][6], b[6][6];
    for (int i = 0; i < 6; i++) for (int j = 0; j < 6; j++) {
        x[i][j] = i + j;
        a[i][j] = i * j;
        b[i][j] = (i + 1) / (j + 1);
    }
    cout << "Part a: " << x[5][4] << endl;
    cout << "Part b: " << a[5][4] << endl;
    cout << "Part c: "; x1(x, 5);
    cout << "Part d: "; x2(x, 5);
    cout << "Part e: "; x2(b, 3);
    return 0;
}

```

Complete the line of output that begins:

Part a:

Part b:

Part c:

Part d:

Part e:

**Problem 203** Write a function called *sixCount* that returns a count of the number of digits that are equal to 6 in its positive integer parameter.

For example, a program that uses the function *sixCount* follows.

```

int main() {
    cout << sixCount(16) << endl;    // prints 1
    cout << sixCount(666) << endl;  // prints 3
    cout << sixCount(777) << endl;  // prints 0
    return 0;
}

```

**Answer:**



**Problem 204** Write a complete C++ program that does the following.

1. It asks the user to enter a positive integer  $n$  that is at most 100.
2. The program reads in an array  $n$  integers entered by the user.
3. The program prints the negative entries from the array, in order.
4. The program prints the positive entries from the array in reverse order.

For example, the following represents one run of the program.

```
Enter a positive integer (at most 100):      8
Enter 8 integers:  3 -1 4 -10 17 18 19 -11
-1 -10 -11
19 18 17 4 3
```

**Answer:**

**Problem 205** Write C++ statements to carry out the following tasks. **Do not write complete programs**, just give a single line, or a few lines of C++ instructions. Assume that the following variables have been declared, and if necessary have values, for each part:

```
int x[10], y[10], z[10][10], r, c;
```

- (i) Read 10 integers into the array  $x$ .
- (ii) Set all the entries of the array  $z$  so that the entry in row  $r$  and column  $c$  stores the product of  $r$  and  $c$ .
- (iii) Print the smallest value in the array  $x$ .
- (iv) Print the word *Divides* if  $r$  divides exactly into  $c$  otherwise do nothing.
- (v) Swap each entry of the array  $x$  with the corresponding entry of array  $y$ .

**Problem 206** Consider the following C++ program.

```
#include <iostream>
using namespace std;

int recursive(int n) {
    if (n < 100) return n%10;
    return 10 * recursive(n / 100) + n % 10;
}

main() {
    int x;
    cout << "Enter an integer: ";
    cin >> x;
    cout << recursive(x) << endl;
    return 0;
}
```

What is the output from the program in response to the following user inputs.

- (a) The user enters -10 for  $x$ .
- (b) The user enters 5 for  $x$ .
- (c) The user enters 55 for  $x$ .
- (d) The user enters 123 for  $x$ .
- (e) The user enters 19683 for  $x$ .

**Problem 207** Write a function called *toTen* that calculates how many entries of an array need to be added to make a sum of 10 or more. (Start adding from index 0.)

For example, a program that uses the function *toTen* follows.

```
int main() {
    int x[8] = {5, 3, 1, 6, 10, 1, -30, -100};
    cout << toTen(x, 8) << endl;
    return 0;
}
```

The output from this program would be 4, because the sum of the first 4 entries  $5 + 3 + 1 + 6$  is the first sum that exceeds 10.

**Answer:**

**Problem 208** Write a complete C++ program that does the following.

1. It asks the user to enter their name as a string *name*.
2. The program reads the name entered by the user.
3. The program converts all letters in the name to uppercase and prints the name.
4. The program prints the uppercase characters of the name in reverse.

For example, the following represents one run of the program.

```
What is your name:   Freddy
FREDDY
YDDERF
```

**Answer:**

**Problem 209** Write header lines (prototypes) for the following functions. Do not supply the blocks for the functions.

- (a) A function called **sumDigits** which returns the sum of the digits of an integer.

**Answer:**

- (b) A function called **isSmall** that returns an answer of true if a double precision parameter has a value between 0 and 0.001. (It returns false otherwise.)

**Answer:**

- (c) A function called **randomLetter** which generates and returns a random letter of the alphabet. (The output is to be a single character between 'A' and 'Z'.)

**Answer:**

- (d) A function called **sort3** which is to change a collection of three input values so that they appear in increasing order.

**Answer:**

- (e) A function called **total** which is to determine the sum of all the entries in an array.

**Answer:**

**Problem 210** Consider the following C++ program.

```

#include <iostream>
using namespace std;

int recursive(int n) {
    if (n < 10) return n;
    return n % 10 - recursive(n/10);
}

main() {
    int x;
    cout << "Enter a positive integer: ";
    cin >> x;
    if (x <= 0) cout << "Error" << endl;
    else cout << recursive(x) << endl;
    return 0;
}

```

What is the output from the program in response to the following user inputs.

- (a) The user enters 0 for x.
- (b) The user enters 5 for x.
- (c) The user enters 55 for x.
- (d) The user enters 555 for x.
- (e) The user enters 19683 for x.

**Problem 211** Write a function called *quadratic* that calculates the value of a quadratic function  $ax^2 + bx + c$ . For example, a program that uses the function *quadratic* follows.

```

int main() {
    double a = 1.0, b = 2.2, c = 1.21, x = 0.1;
    cout << quadratic(a, b, c, x) << endl;
    return 0;
}

```

**Answer:**

**Problem 212** Write a complete C++ program that does the following.

1. It asks the user to enter a positive integer value,  $n$ .
2. The program reads a value entered by the user. If the value is not positive, the program should terminate.
3. The program should consider every number  $x$  between 1 and  $n$  and print out any value of  $x$  that divides exactly into  $n$ .

The printed values should all appear on a single line, separated by spaces.

For example, the following represents one run of the program. (The user chooses the number 28.)

```

Enter a positive integer:    28
1 2 4 7 14 28

```

**Answer:**

**Problem 213** Write header lines (prototypes) for the following functions. Do not supply the blocks for the functions.

(a) A function called **sum** which returns the sum of 4 double precision values.

**Answer:**

(b) A function called **midDigit** that is used to return the middle digit of an integer.

**Answer:**

(c) A function called **isPositive** which is to return an answer of true if the sum of the entries of an array of double precision data is positive (and return false otherwise).

**Answer:**

(d) A function called **average2DArray** which is to print (to cout) the average of the entries in a 2-dimensional array (the array stores integers and has 10 rows and 15 columns).

**Answer:**

(e) A function called **makeZero** which is to use two integer input variables and change their values to zero. (After the function ends, the input variables must be zero.)

**Answer:**

**Problem 214** Consider the following C++ program.

```
#include <iostream>
using namespace std;

void mystery(int n) {
    cout << n % 100;
    if (n < 1000) return;
    mystery(n/10);
}

main() {
    int x;
    cout << "Enter an integer: ";
    cin >> x;
    mystery(x);
    cout << endl;
    return 0;
}
```

What is the output from the program in response to the following user inputs.

(a) The user enters 5 for x.

(b) The user enters 512 for x.

(c) The user enters 4370 for x.

(d) The user enters 175560 for x.

**Problem 215** Write a function called *sum2D* that returns the sum of all elements in a 2-dimensional array that has 4 columns of integer entries.

For example, a program that uses the function *sum2D* follows.

```
int main() {
    int array[3][4] = {{1,2,3,4},{1,2,3,4},{1,2,3,4}};
    cout << sum2D(array, 3, 4) << endl;
    return 0;
}
```

The input values 3 and 4 specify the number of rows and columns in the array. The program should print an answer of 30 (since this is the sum of 1, 2, 3, 4, 1, 2, 3, 4, 1, 2, 3, and 4).

**Answer:**

**Problem 216** Write a complete C++ program that does the following.

1. It asks the user to enter a 5-digit integer value,  $n$ .
  2. The program reads a value entered by the user. If the value is not in the right range, the program should terminate.
  3. The program calculates and stores the 5 individual digits of  $n$ .
  4. The program outputs a “bar code” made of 5 lines of stars that represent the digits of the number  $n$ .
- For example, the following represents one run of the program. (The user chooses the number 16384.)

```
Enter a 5 digit integer:    16384
*
*****
***
*****
***
```

**Answer:**

**Problem 217** Write header lines (prototypes) for the following functions. Do not supply the blocks for the functions.

- (a) A function called **lastDigit** that is used to find the last digit of an integer.

**Answer:**

- (b) A function called **average** which determines the average of 3 integer values.

**Answer:**

- (c) A function called **largest** which is used to find the largest value in an array of double precision data.

**Answer:**

- (d) A function called **print2DArray** which is to print out all of the data in a 2-dimensional array (the array has 100 columns).

**Answer:**

- (e) A function called **sort** which is to sort an array of strings into alphabetical order.

**Answer:**

**Problem 218** Consider the following C++ program.

```

#include <iostream>
using namespace std;

void mystery(int data[], int p, int q) {
    data[p] = data[q];
    data[q] = data[p];
}

void m2(int p, int q) {
    int temp = p;
    q = p;
    p = temp;
}

void print(int data[], int p) {
    for (int i = 0; i < p; i++)
        cout << data[i] << " ";
    cout << endl;
}

main() {
    int scores[8] = {3, 1, 4, 1, 5, 9, 2, 6};
    int quiz[7] = {0, 1, 2, 3, 4, 5, 6};
    print(scores, 3);
    print(quiz, 4);
    mystery(scores, 1, 2);
    print(scores, 5);
    for (int i = 0; i < 3; i++)
        m2(quiz[i], quiz[i+ 1]);
    print(quiz, 6);
}

```

What is the output from the program?

**Problem 219** Write a function called *countChange* that uses four parameters *q*, *d*, *n*, and *p* and converts the value of *q* quarters, *d* dimes, *n* nickels, and *p* cents into dollars.

For example, a program that uses the function *countChange* follows.

```

int main() {
    int q = 10, d = 5, n = 1, p = 2;
    double x = countChange(q, d, n, p);
    cout << "You have $" << x << endl;
}

```

It should print:

You have \$3.07

**Answer:**

**Problem 220** Write a complete C++ program that does the following.

1. It asks the user to enter a positive integer value, *r* that is at most 100.
2. The program reads a value entered by the user. If the value is not in the right range, the program should terminate.
3. The program reads and stores *r* integers from the user and then prints a pattern of *r* rows of stars, the lengths of which are the other integers entered by the user.

For example, the following represents one run of the program.

```
How many rows? 4
Enter 4 row lengths: 2 7 1 5
**
*****
*
*****
```

**Answer:**

**Problem 221** Write a C++ program that asks a user how many times it should say hello and then says hello the required number of times. For example, a run of the program might produce the following output:

```
How many hellos do you want: 6
Hello Hello Hello Hello Hello Hello
```

**Problem 222** Two numbers are considered as very different if they differ by more than 10. Write a C++ function called `areVeryDifferent` that determines whether two integers are very different.

For example, your function could be used in the following program.

```
int main() {
    int x = 4, y = 10, z = -4;
    if (areVeryDifferent(x, y)) cout << "x and y are very different" << endl;
    if (areVeryDifferent(x, z)) cout << "x and z are very different" << endl;
    if (areVeryDifferent(y, z)) cout << "y and z are very different" << endl;
    return 0;
}
```

The output from this program would be:

```
y and z are very different
```

**Problem 223** Write a complete C++ program that does the following.

1. It asks the user to enter a positive integer value,  $x$  that is at most 100.
2. The program reads a value entered by the user. If the value is not in the right range, the program should terminate.
3. The program reads and stores  $x$  words from the user and then prints them in reverse order.

For example, the following represents one run of the program.

```
How many words? 5
Freddy and Max were absent
absent were Max and Freddy
```

**Answer:**

**Problem 224** Consider the following C++ program.

```
#include <iostream>
using namespace std;

void mystery(int data[], int p, int q) {
    data[p] = data[q] + data[p];
    data[q] = 0;
}

void print(int data[], int p) {
    for (int i = 0; i < p; i++)
        cout << data[i] << " ";
    cout << endl;
}

main() {
    int scores[8] = {3, 1, 4, 1, 5, 9, 2, 6};
    int quiz[7] = {0, 1, 2, 3, 4, 5, 6};
    print(quiz, 7);
    print(scores, 8);
    mystery(scores, 3, 4);
    print(scores, 8);
    for (int i = 1; i < 7; i++)
        mystery(quiz, 0, i);
    print(quiz, 7);
}
```

What is the output from the program?